



Catalog No. TM4020CCU

Description: 200A 40CT 1P3W 120/240V 22K IC COMB

UPC No 783164112627

 $\label{eq:home} \textbf{Home} > \textbf{Load Centers} > \textbf{Single Phase - USA}$

PowerMark Gold main breaker load centers arrive with a main breaker installed for a convenient and swift install. Main breakers allow for the user to stop the flow of electricity in the load center, shutting off all the power in the residence. The TM4020CCU features spaces for 40, 1" breakers, a 200 A bus ampere rating, a copper bus, and a combination surface/flush enclosure.

Descriptors	
Category	Single Phase - USA
Category GO Schedule	RD
6 16 11	

Specifications			
Input/Output Voltage	120/240V ac		
Туре	Standard		
Interrupting Capacity Rating	22		
Amperage	200 A		
Device type	Main Breaker		
Enclosure	Indoor Type 1 Enclosure, Combination		
Phase	1 Phase		
1" Space	40		
1/2" Space	0		
Feed	Either		
Door	Yes		
GSA Compliance	Yes		
NEMA Rating	NEMA 1		
Circuit Breaker Style	Plug-In		

Classifications	
UL/CUL Listing	UL

electrification.us.abb.com Created on: 05/14/2022

Publications		
Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers	DET1000	Application and Technical
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	
1 page outline drawing in pdf format.	10103091SH23	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

electrification.us.abb.com Created on: 05/14/2022