

# SECURITY ALARM CABLE | PLENUM UNSHIELDED



AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	SOL	982202	31	.018	.45	.118	3.00	9
	2	7	912202	31	.015	.38	.116	2.95	12
	3	7	912203	31	.015	.38	.123	3.12	15
	4	SOL	982204	31	.018	.45	.136	3.45	16
	4	7	912204	31	.015	.38	.134	3.40	19
	6	7	912206	31	.015	.38	.158	4.01	24
	8	7	912208	31	.015	.38	.169	4.24	30
	10	7	912210	31	.015	.38	.186	4.72	37
20	12	7	912212	31	.015	.38	.200	5.08	42
	2	7	912002	33	.015	.38	.138	3.51	15
	3	7	912003	33	.015	.38	.143	3.63	21
	4	7	912004	33	.015	.38	.160	4.06	24
18	2	7	911802	34	.015	.38	.157	3.99	22
	3	7	911803	34	.015	.38	.168	4.27	28
	4	7	911804	34	.015	.38	.186	4.72	36
	5	7	911805	34	.015	.38	.203	5.16	41
	6	7	911806	34	.015	.38	.211	5.36	51
	8	7	911808	34	.015	.38	.242	6.15	65
	9	7	911809	34	.015	.38	.256	6.50	68
	10	7	911810	34	.015	.38	.260	6.60	75
16	12	7	911812	34	.015	.38	.283	7.19	89
	2	19	911602	38	.015	.38	.180	4.57	26
	3	19	911603	38	.015	.38	.191	4.85	38
14	4	19	911604	38	.015	.38	.211	5.36	47
	2	19	911402	39	.015	.38	.222	5.64	40
12	3	19	911403	39	.015	.38	.236	5.99	60
	4	19	911404	39	.015	.38	.261	6.63	75
12	2	19	911202	42	.015	.38	.257	6.53	58
	4	19	911204	42	.015	.38	.312	7.93	108

## PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted with an overall low smoke white PVC jacket\* with rip cord.

## APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

## SPECIFICATIONS

**Conductor** Bare Copper

**Insulation** Low Smoke PVC

- 22 AWG .007" PVC
- 20 AWG .008" PVC
- 18 AWG .009" PVC
- 16 AWG .010" PVC
- 14-12 AWG .012" PVC

**Jacket** Low Smoke PVC

**NEC Articles**

- 22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P

**Voltage Rating** 300 V

**Temp. Rating** -25°C to 75°C

## COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

## AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

## CABLE IDENTIFICATION

XX AWG XC (UL) TYPE CL3P/  
FPLP c(UL)us TYPE CMP E179335

\*Other colors available upon request. Please consult factory for minimums and lead times.

\*14-12 AWG are not recognized by c(UL).

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to [www.adcable.com](http://www.adcable.com) for the most up to date information. Rev 0419



(800) 343 2579 • [www.adcable.com](http://www.adcable.com)