



## Catalog No. R011C010

Description: 100A SURFACE MTRD 20/20GFCI

UPC No 784567204971

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors		
Category	Temporary Power	
Specifications		
Mounting	Surface	
Heads	Surface	
Metering	Ringless	
Receptacles	20GFCI/20GFCI	
Feed	Overhead	
AIC	10,000	
Amps	100.0 A	
Cabinet Size	9 X 30	
Circuit Protection	Yes	
Hub Provision	Yes	
Installed Breaker	(2) CB120	
Load Center	LC33N1	
Loop Feed	No	
Phase	1	
Unit Weight	21.0 lb	
Volts	120/240	
Classifications		
Stock Class Code	Stock	
Approvals		
Certification	UL/CUL	

midwestelectric.com Created on: 12/13/2021

Publications		
Title	<b>Publication No.</b>	<b>Publication Type</b>
Storm Season Brochure		
This brochure highlights the most popular products sold during storm season.	MET1005	Brochures
Storm Season Brochure		
This brochure highlights the most popular products sold during storm season.	005	Brochures
Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Outline Drawing	R011C010	Drawings-Outline and Dimensional
Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Top 120V 1PH G90 N3R Outline Drawing		

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

midwestelectric.com Created on: 12/13/2021