



Part Number: 912202
Description: 22 AWG two conductor plenum rated
Suitable Application: Sound, Audio, Security, and Data Communication

Construction Details:

Total Number Conductors	2
AWG	22
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation/Dielectric Thickness	.007"
Nominal Insulation Diameter	.043"
Color Code	Black/Red
Cabling Overall Lay	2 1/2" left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White
Nominal Jacket Diameter	.116"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Print Generic Sample Legend:

22 AWG 2C (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E179335

Electricals:

Voltage Rating	300 volts
Capacitance CDR	20.5 pF/ft
Conductors	ASTM B-8
Temperature Rating:	-4C to +75°C

Applicable Standards:

ETL Type	CMP, CL3P, FPLP
UL Type	CMP, CL3P, FPLP
ROHS Compliant	Yes

Customer Name: _____ Date Signed: _____

Customer Approval: _____

Specification Issue Date: 3/6/12

Rev. 08/28/17