

Eaton DG1-34023FB-C21C

Catalog Number: DG1-34023FB-C21C

Eaton PowerXL DG1 variable frequency drive, 380-500V input 11 kW 15 Hp CT 3PH 50/60 Hz 23A output IP21/type 1 FR3 LCD Internal EMC filter and DC choke EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU ports 2 exp slots Brake chopper

General specifications



Product Name	Catalog Number
Eaton PowerXL DG1 variable frequency drive	DG1-34023FB-C21C
	UPC
	786685878768

Product Length/Depth	Product Height
21 in	14 in

Product Width	Product Weight
10 in	26.2 lb

Warranty	Compliances
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.	C-Tick Compliant RoHS Compliant CE Marked GoST-R

Certifications
UL 508C EN 61800-5-1 IEC 61508 EN 62061 EN ISO 13849-1 EN 61800-3 cUL Listed UL Listed

Product specifications

Max overload

110% for 1 minute

High overload (CT) amps

23 A

Phase

Three-phase in, three-phase out

Motor control modes

Frequency, Speed, Open-loop speed, Open-loop torque

Internal DC choke

Yes

Conformal coated boards

Yes

Low overload (VT) kW

15 kW

Enclosure

IP21/type 1

Number of slots

2 expansion slots

Communications onboard

EtherNet/IP, Modbus TCP, RS-485: Modbus RTU, BACnet MS/TP

Motor type

Inductio, PM (IPM & SPM)

Electromagnetic compatibility filter

EMC Filter

User interface

Graphical Keypad

Brake chopper

Brake chopper

Input output

400 Vac (380-500 Vac)

Power consumption

11 kW

High overload (CT) kW

11 kW

Resources

Application notes

Real time clock and use of the timers

PID controller

Motor data and V/f curves

Load balancing in multi motor applications

Digital I/Os

Smoke Mode and fire mode

Torque control

Connecting drives to generator supplies

Operating at low temperatures

Electromagnetic compatibility (EMC)

Analog I/Os

Dual Rating What exactly does that mean?

Starting, stopping and operation

DG1 in pump and fan applications

Catalogs

Eaton's Volume 6—Solid-State Motor Control

Product Range Catalog Drives Engineering

Data sheet

Drawings

DG1_FB_(FR2-UL) 3D Inventor

DG1_FB_(FR2-UL) 3D Model Xchange

DG1_FB_(FR2-UL) AutoCAD 2D Footprint

DG1_FB_(FR2-UL) AutoCAD 2D Footprint (mm)

DG1_FB_(FR2-UL) 2D Drawing Xchange

Installation instructions

PowerXL DG1 Series VFD Installation Manual

PowerXL DG1 Series VFD Application Manual

Specifications and datasheets

Eaton Specification Sheet - DG1-34023FB-C21C

Horsepower

15 hp

Frequency rating

50-60 Hz

Protection

Internal EMC filter, DC choke

Communication

EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication

Input voltage

400 V, 380-500 V(-15%, +10%)

Material

Coated board

Low overload (VT) hp

20 hp

Output current - max

23 A

Low overload (VT) amps

31 A

High overload (CT) hp

15 hp

Frame size

3

Output frequency range

0 - 400 Hz

Input voltage range

380 - 500 V

Recommended fuse size

35

Keypad

Included

Input frequency range

50 - 60 Hz

Software

Active energy control, quick start wizard

Torque rating

CT

Display

LCD graphical



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)