

Multi-Conductor Cables

Overall Shield

- Conductors:** Stranded Tinned Copper
Insulation: Polyethylene
Shield: Aluminum Mylar overall shield with stranded tinned copper drain wire
Jacket: PVC
Construction: Cabled
Temperature Rating: 60°C
Operating Voltage: 300V
Applications: Control cable for power limited circuits. Processing equipment, audio, and other low voltage control uses requiring cable with excellent electrical characteristics.
Approvals: UL Type CM
 NEC Article 800
 AWM Style as noted



Part Number	AWG	Number of Conductors	Copper Stranding	Drain Wire AWG	Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal O. D.	Color Code	AWM Style	Nominal Cap. PI/Ft. * **	Weight Per 1000 Ft.
672202	22	2	7 x 30	22 AWG	.016"	.025"	.177"	Blk/Nat	2092	24 47	18
672203	22	3	7 x 30	22 AWG	.016"	.032"	.200"	Blk/rd/Nat	2093	23 41	23
672204	22	4	7 x 30	22 AWG	.016"	.027"	.224"	Blk/Nat/Rd/Gn	2094	24 48	25
672002	20	2	7 x 28	22 AWG	.016"	.028"	.204"	Blk/Nat	2092	27 51	24
672003	20	3	7 x 28	22 AWG	.016"	.033"	.216"	Blk/Nat/Rd	2093	17 51	31
672004	20	4	7 x 28	22 AWG	.016"	.028"	.230"	Blk/Nat/Rd/Gn	2094	27 49	38
671802	18	2	16 x 30	20 AWG	.018"	.030"	.229"	Blk/Nat	2092	24 44	31
671803	18	3	16 x 30	20 AWG	.018"	.026"	.232"	Blk/Rd/Nat	2093	17 48	37
671804	18	4	16 x 30	20 AWG	.018"	.028"	.254"	Blk/Nat/Rd/Gn	2094	27 48	47
671602	16	2	19 x .0117	18 AWG	.032"	.032"	.310"	Blk/Nat	2106	27 47	52
671603	16	3	19 x .0117	18 AWG	.032"	.032"	.349"	Blk/Rd/Nat	2107	26 60	72
671402	14	2	19 x .0147	16 AWG	.032"	.042"	.345"	Blk/Nat	2106	24 47	70
671202	12	2	19 x 25	14 AWG	.037"	.040"	.419"	Blk/Nat	2106	25 49	103

* Conductor to Conductor
 ** Conductor to Shield