

# COMMUNICATION & CONTROL



PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
			INCH	mm	INCH	mm	
<b>4-2402*</b> Equal to Belden™ 9841	<b>24/1pr</b>	7x30 TC	.035	.89	.232	5.89	33
<b>4-2422*</b> Equal to Belden™ 9842	<b>24/2pr</b>	7x30 TC	.035	.89	.340	8.64	51
<b>22002TSD</b> Equal to Belden™ 8761	<b>22/2</b>	7x30 TC	.025	.64	.175	4.44	18
<b>22003TSD</b> Equal to Belden™ 8771	<b>22/3</b>	7x30 TC	.033	.84	.199	5.05	24
<b>22022TSD</b> Equal to Belden™ 8723	<b>22/4</b>	7x30 TC	.025	.64	.160	4.06	19
<b>22033TSD</b> Equal to Belden™ 8777	<b>22/6</b>	7x30 TC	.025	.64	.273	6.93	42
<b>20002TSD</b> Equal to Belden™ 8762	<b>20/2</b>	7x28 TC	.028	.71	.204	5.18	23
<b>20003TSD</b> Equal to Belden™ 8772	<b>20/3</b>	7x28 TC	.033	.84	.218	5.54	32
<b>21802SD</b> Equal to Belden™ 8760	<b>18/2</b>	16/30 TC	.028	.71	.222	5.64	26
<b>21803SD</b> Equal to Belden™ 8770	<b>18/3</b>	16x30 TC	.033	.84	.246	6.25	39
<b>318004SD</b> Equal to Belden™ 9418	<b>18/4</b>	19/30 TC	.035	.89	.245	6.22	49
<b>21602SD</b> Equal to Belden™ 8719	<b>16/2</b>	19x29 TC	.032	.81	.313	7.95	49
<b>14002TSD</b> Equal to Belden™ 8720	<b>14/2</b>	19x27 TC	.035	.89	.355	9.02	71
<b>21202SD</b> Equal to Belden™ 8718	<b>12/2</b>	19x25 TC	.040	1.02	.400	10.2	100

## PRODUCT DESCRIPTION

PVC insulated stranded tinned copper conductors, short overall twist length, aluminum mylar shielding with drain wire and an overall gray PVC jacket.

## SPECIFICATIONS

Conductor	Tinned Copper
Insulation	Equal to competitor
Jacket	PVC
Shield	Aluminum Mylar *90% Tinned Copper Braid
NEC Articles	800 CM 14-12 AWG CL2
Voltage Rating	300 V
Temp. Rating	75°C
Drain Wire	Equal to competitor

## APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

## COLOR CODE CHART

\*Equal to competitor

## AVAILABLE PUT-UPS

1,000' Reels and Boxes  
500' Reels and Boxes  
Other lengths available. Please consult your factory representative for availability.

Plenum Options Available Upon Request



Belden™ is a trademark of Belden Inc.

The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable. ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice. REV0618

PHONE: (800) 343 2579 • FAX: (828) 389 3922 • WWW.ADCABLE.COM