



Representative Image

## Catalog No. TLM4020CCUG

**Description: 200A 40CT 1P3W 22K IC FLD CONV WGRND BR**

**UPC No 783164491241**

**Home > Load Centers > Single Phase - USA**

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM4020CCUG features space for 40, 1" breakers, 200 A bus ampere rating, a copper bus, a factory installed ground bar, and a combination/flush enclosure.

### Descriptors

Category	Single Phase - USA
----------	--------------------

### Specifications

Input/Output Voltage	120/240V ac
Amperage	200 A
Device type	Main Lug
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	1 Phase
1" Space	40
1/2" Space	0
Feed	Either
Door	Yes
NEMA Rating	NEMA 1
Circuit Breaker Style	Plug-In

### Classifications

UL/CUL Listing	UL
----------------	----

## Publications

Title	Publication No.	Publication Type
<a href="#">Section 1 BuyLog: Load centers and circuit breakers</a> Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.