

# Galvanized Rigid Conduit (GRC) Couplings

## Features:

- Hot-dip galvanized for excellent corrosion resistance
- High strength ductile steel for long life and easy bending
- Smooth, continuous raceways for fast wire pulling
- Kwik-Release End Cap to protect threads
- Listed to Safety Standard UL 6
- Manufactured in accordance with ANSI C80.1
- Available in trade sizes 1/2" (16 mm) - 6" (155 mm)

## Standards:


- Precision manufacturers for dependable, long-lasting value and ultimate protection for electrical conductors
- Highly resistant to damage from impact (Article 344 NEC)
- Recognized as equipment grounding conductor (Sec 250.118 NEC)
- UL Safety Standard 6



## Galvanized Rigid Conduit (GRC) Couplings

Listed to Safety Standard UL 6

Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Nominal OD (A) <sup>1</sup>		Length (B) <sup>1</sup>		Threads Per Inch <sup>1</sup>	Approximate Weight Per 100 Pieces		Standard Package
		(in)	(mm)	(in)	(mm)		(lb)	(kg)	
1/2	16	1.01	25.7	1 <sup>5</sup> / <sub>8</sub>	41.3	14	12	5.4	100
3/4	21	1.25	31.8	1 <sup>4</sup> <sup>1</sup> / <sub>4</sub>	41.7	14	18	8.2	50
1	27	1.53	38.7	1 <sup>3</sup> <sup>1</sup> / <sub>2</sub>	50.0	11 <sup>1</sup> / <sub>2</sub>	30	13.6	30
1 <sup>1</sup> / <sub>4</sub>	3w5	1.87	47.5	2 <sup>1</sup> / <sub>2</sub>	51.6	11 <sup>1</sup> / <sub>2</sub>	37	16.8	25
1 <sup>1</sup> / <sub>2</sub>	41	2.16	54.7	2 <sup>1</sup> / <sub>16</sub>	52.4	11 <sup>1</sup> / <sub>2</sub>	52	23.6	25
2	53	2.65	67.3	2 <sup>1</sup> / <sub>8</sub>	54.0	11 <sup>1</sup> / <sub>2</sub>	72	32.7	20
2 <sup>1</sup> / <sub>2</sub>	63	3.25	82.6	3 <sup>3</sup> / <sub>16</sub>	81.0	8	170	77.1	1
3	78	3.87	98.3	3 <sup>5</sup> / <sub>16</sub>	84.1	8	210	95.3	1
3 <sup>1</sup> / <sub>2</sub>	91	4.50	114.3	3 <sup>13</sup> / <sub>32</sub>	86.5	8	340	154.2	1
4	103	4.88	123.8	3 <sup>33</sup> / <sub>64</sub>	89.3	8	300	136.1	1
5	129	6.00	152.4	3 <sup>61</sup> / <sub>64</sub>	100.4	8	475	215.5	1
6	155	7.20	182.9	4 <sup>1</sup> / <sub>4</sub>	108.0	8	765	347.0	1

<sup>1</sup>Minimum requirement as per UL Standard

