



SKU: CSWS-6-10

UPC: 0783669628937

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 6, 1 Hole, #10 Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

| | |
|---------------------------|-------------|
| Barrel Marking | Ink |
| Barrel Type | Standard |
| Connecting Angle | 180° |
| Connection | Compression |
| Contains DE-OX® | No |
| Flared End | No |
| ILSCOs Die Catalog Number | ILD-24 |
| ILSCOs Die Index Number | I-24 |
| Mounting Hole Type | Thru |
| Narrow Tang | No |
| Number of Mounting Holes | 1 |
| Sight Window | Yes |
| Slotted | No |
| Tang End Shape | Square |
| Undrilled | No |

Dimensions

| | |
|------------------------------|---------|
| Barrel Length (IN) | 0.5 |
| Barrel Length (mm) | 12.7 |
| Dimension G (IN) | 0.258 |
| Dimension G (mm) | 6.5532 |
| Height (IN) | 0.343 |
| Height BX (IN) | 2.25 |
| Height (mm) | 8.7122 |
| Inside Diameter (IN) | 0.313 |
| Inside Diameter (mm) | 7.9502 |
| Length (IN) | 1.257 |
| Length (mm) | 31.9278 |
| Mounting Bolt/Stud Size (mm) | 254 |
| Mounting Hole Diameter (IN) | 0.219 |
| Mounting Hole Diameter (mm) | 5.5626 |
| Mounting Hole Spacing (mm) | 0 |
| Outside Diameter (IN) | 0.225 |
| Outside Diameter (mm) | 5.715 |
| Strip Length (mm) | 14.2748 |
| Tang Length (IN) | 0.562 |
| Tang Length (mm) | 14.2748 |
| Tang Thickness (IN) | 0.087 |
| Tang Thickness (mm) | 2.2098 |

| | |
|-----------------|-------------------|
| Tang Width (IN) | 0.44 |
| Tang Width (mm) | 11.176 |
| Weight (LB) | 0.013660859249861 |
| Weight BX (LB) | 1.57 |
| Width (IN) | 0.44 |
| Width BX (IN) | 5 |
| Width (mm) | 11.176 |

Conductor Ranges

| | |
|--|-----------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | 6 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 6 Str |
| Conductor Range AL Solid (Primary, run, main, line) | NA |
| Expanded Conductor Range | NA |
| Flex Conductor Range | 6 G,H,I,K,M,DLO |

Material and Finish

| | |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish | Tin |
| Insulation | NA |
| Material | Copper |

Additional Technical Specifications

| | |
|----------------|------|
| Conductor Type | Flex |
|----------------|------|

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial | Yes |
| Dual Rated | No |
| NEMA Code | S-588-3 |
| UPC Code | 78366962893 |

Bolt and Screw Sizes

| | |
|-------------------------|-----|
| Mounting Bolt/Stud Size | #10 |
|-------------------------|-----|

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | LR-29601 |
| CSA Standard | C22.2 No. 65-03 |
| NEBS Rating | Level 3 |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator | IND |
| UL Control Number | 453G |
| UL / CULUS Specification | UL 486A/B Listed |
| UL File Number | E6207 |

Environment and Temperature

Temperature Rating 90°C

Color

| | |
|------------|--------|
| Color | Silver |
| Color Code | Blue |

Voltage

Voltage Rating 35 kV