



4 In. Square Box, Welded, 2-1/8 In. Deep, Ten 1/2 In KO's & Six TKO's, Raised Ground. 10 In. #12 Stranded Copper Pigtail

Catalog #: 232SM



FEATURE BENEFIT

Welded 4 In. square box for installing receptacles, switches or fixtures in walls or ceilings

PRODUCT FEATURES

- · Combination screw heads allow quick installation
- Welded construction
- Eight 1/2 In. knockouts and four TKO knockouts
- 30.3 Cu. In. capacity
- Raised ground, 10 In. #12 stranded copper pigtail
- Acceptable in 2-hour fire rated walls

APPLICATIONS

Designed to enclose electrical wiring, switches, receptacles or lighting fixtures. Constructed from 1/16 In. pre-galvanized steel. 8-32 cover mounting screws assembled. Suitable for use without a bonding jumper in circuits up to 600V.

CERTIFICATIONS



PRODUCT SPECIFICATIONS

UPC Number:
Ea Length/Depth (in.):
Ea Width (in.):
Ea Height (in.):
Wt. Ea. (Lbs.):
Package Type:
Product UPC-A Labeled:

050169982327 2.438 4.00 4.00 0.947 Loose Yes

SHIPPING

Case I2of5: Standard Carton Qty: Min Order Qty:

HUBBELL

50050169982322 25 25

RACO

574-234-7151

3902 W. Sample St. South Bend, IN 46619

www.hubbell.com/raco/en





All RACO single-gang, two-gang, 4 In. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com

600V

Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

vision 1 Entrugry 2020



©2020 Hubbell. All rights reserved. Information subject to change. Trademarks are property of their respective owners.

COMMERCIAL

CONSTRUCTION A Division of Hubbell Incorporated (Delaware)

RA_SPEC-SHEET