

Galvanized Rigid Conduit (GRC) Nipples



Features:

- Hot-dip galvanized for excellent corrosion resistance
- High strength ductile steel for long life and easy bending
- Smooth, continuous raceways for fast wire pulling
- Kwik-Release End Cap to protect threads
- Listed to Safety Standard UL 6
- Manufactured in accordance with ANSI C80.1
- Available in trade sizes 1/2" (16 mm) - 6" (155 mm)


Standards:

- Precision manufacturers for dependable, long-lasting value and ultimate protection for electrical conductors
- Highly resistant to damage from impact (Article 344 NEC)
- Recognized as equipment grounding conductor (Sec 250.118 NEC)
- UL Safety Standard 6

Galvanized Rigid Conduit (GRC) Nipples

Listed to Safety Standard UL 6

Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Length (A)		Total Thread Length ¹		Threads Per Inch ¹	Approximate Weight Per 100 Pieces		Standard Package
		(in)	(mm)	(in)	(mm)		(lb)	(kg)	
1/2	16	(Close) 1 1/8	29	0.78	19.8	14	6	2.7	25
1/2	16	1 1/2	38	0.78	19.8	14	8	3.6	25
1/2	16	2	51	0.78	19.8	14	12	5.4	25
1/2	16	2 1/2	64	0.78	19.8	14	15	6.8	25
1/2	16	3	76	0.78	19.8	14	19	8.6	25
1/2	16	3 1/2	89	0.78	19.8	14	22	10.0	25
1/2	16	4	102	0.78	19.8	14	26	11.8	25
1/2	16	5	127	0.78	19.8	14	33	15.0	25
1/2	16	6	152	0.78	19.8	14	40	18.1	25
1/2	16	8	203	0.78	19.8	14	54	24.5	25
1/2	16	10	254	0.78	19.8	14	68	30.8	25
1/2	16	12	305	0.78	19.8	14	82	37.2	25

¹Minimum requirement as per UL Standard

Chart continued on next page




Galvanized Rigid Conduit (GRC) Nipples

Trade Size	Metric Designator	Length (A)		Total Thread Length ¹		Threads Per Inch ¹	Approximate Weight Per 100 Pieces		Standard Package
		(in)	(mm)	(in)	(mm)		(lb)	(kg)	
3/4	21	(Close) 1 3/8	35	0.79	20.1	14	9	4.1	25
3/4	21	1 1/2	38	0.79	20.1	14	10	4.5	25
3/4	21	2	51	0.79	20.1	14	14	6.4	25
3/4	21	2 1/2	64	0.79	20.1	14	19	8.6	25
3/4	21	3	76	0.79	20.1	14	24	10.9	25
3/4	21	3 1/2	89	0.79	20.1	14	28	12.7	25
3/4	21	4	102	0.79	20.1	14	34	15.4	25
3/4	21	5	127	0.79	20.1	14	43	19.5	25
3/4	21	6	152	0.79	20.1	14	52	23.6	25
3/4	21	8	203	0.79	20.1	14	73	33.1	25
3/4	21	10	254	0.79	20.1	14	89	40.4	25
3/4	21	12	305	0.79	20.1	14	109	49.4	25
1	27	(Close) 1 1/2	38	0.98	24.9	1 1/2	16	7.3	25
1	27	2	51	0.98	24.9	1 1/2	22	10.0	25
1	27	2 1/2	64	0.98	24.9	1 1/2	28	12.7	25
1	27	3	76	0.98	24.9	1 1/2	36	16.3	25
1	27	3 1/2	89	0.98	24.9	1 1/2	43	19.5	25
1	27	4	102	0.98	24.9	1 1/2	49	22.2	25
1	27	5	127	0.98	24.9	1 1/2	64	29.0	25
1	27	6	152	0.98	24.9	1 1/2	78	35.4	25
1	27	8	203	0.98	24.9	1 1/2	109	49.4	25
1	27	10	254	0.98	24.9	1 1/2	138	62.6	25
1	27	12	305	0.98	24.9	1 1/2	166	75.3	25
1 1/4	35	(Close) 1 3/8	41	1.01	25.7	1 1/2	22	10.0	25
1 1/4	35	2	51	1.01	25.7	1 1/2	28	12.7	25
1 1/4	35	2 1/2	64	1.01	25.7	1 1/2	37	16.8	25
1 1/4	35	3	76	1.01	25.7	1 1/2	47	21.3	25
1 1/4	35	3 1/2	89	1.01	25.7	1 1/2	55	24.9	25
1 1/4	35	4	102	1.01	25.7	1 1/2	66	29.9	25
1 1/4	35	5	127	1.01	25.7	1 1/2	84	38.1	25
1 1/4	35	6	152	1.01	25.7	1 1/2	100	45.4	25
1 1/4	35	8	203	1.01	25.7	1 1/2	136	61.7	25
1 1/4	35	10	254	1.01	25.7	1 1/2	176	79.8	40
1 1/4	35	12	305	1.01	25.7	1 1/2	216	98.0	30
1 1/2	41	(Close) 1 3/4	44	1.03	26.2	1 1/2	28	12.7	25
1 1/2	41	2	51	1.03	26.2	1 1/2	34	15.4	25
1 1/2	41	2 1/2	64	1.03	26.2	1 1/2	44	20.0	25
1 1/2	41	3	76	1.03	26.2	1 1/2	56	25.4	25
1 1/2	41	3 1/2	89	1.03	26.2	1 1/2	68	30.8	25
1 1/2	41	4	102	1.03	26.2	1 1/2	80	36.3	25
1 1/2	41	5	127	1.03	26.2	1 1/2	103	46.7	25
1 1/2	41	6	152	1.03	26.2	1 1/2	122	55.3	50
1 1/2	41	8	203	1.03	26.2	1 1/2	170	77.1	40
1 1/2	41	10	254	1.03	26.2	1 1/2	216	98.0	30
1 1/2	41	12	305	1.03	26.2	1 1/2	260	117.9	20

Galvanized Rigid Conduit (GRC) Nipples

Listed to Safety Standard UL 6
Manufactured in accordance with ANSI C80.1



¹Minimum requirement as per UL Standard




Galvanized Rigid Conduit (GRC) Nipples

Trade Size	Metric Designator	Length (A)		Total Thread Length ¹		Threads Per Inch ¹	Approximate Weight Per 100 Pieces		Standard Package
		(in)	(mm)	(in)	(mm)		(lb)	(kg)	
2	53	(Close) 2	51	1.06	26.9	11½	44	20.0	25
2	53	2½	64	1.06	26.9	11½	59	26.8	25
2	53	3	76	1.06	26.9	11½	72	32.7	25
2	53	3½	89	1.06	26.9	11½	88	39.9	40
2	53	4	102	1.06	26.9	11½	103	46.7	40
2	53	5	127	1.06	26.9	11½	132	59.9	40
2	53	6	152	1.06	26.9	11½	160	72.6	30
2	53	8	203	1.06	26.9	11½	220	99.8	20
2	53	10	254	1.06	26.9	11½	285	129.3	20
2	53	12	305	1.06	26.9	11½	335	152.0	15
2½	63	(Close) 2¾	70	1.57	39.9	8	84	38.1	1
2½	63	3	76	1.57	39.9	8	100	45.4	1
2½	63	3½	89	1.57	39.9	8	120	54.4	1
2½	63	4	102	1.57	39.9	8	150	68.0	1
2½	63	5	127	1.57	39.9	8	197	89.4	1
2½	63	6	152	1.57	39.9	8	240	108.9	1
2½	63	8	203	1.57	39.9	8	329	149.2	1
2½	63	10	254	1.57	39.9	8	422	191.4	1
2½	63	12	305	1.57	39.9	8	505	229.1	1
3	78	(Close) 2⅝	67	1.63	41.4	8	118	53.5	1
3	78	3	76	1.63	41.4	8	130	59.0	1
3	78	3½	89	1.63	41.4	8	157	71.2	1
3	78	4	102	1.63	41.4	8	200	90.7	1
3	78	5	127	1.63	41.4	8	260	117.9	1
3	78	6	152	1.63	41.4	8	300	136.1	1
3	78	8	203	1.63	41.4	8	411	186.4	1
3	78	10	254	1.63	41.4	8	528	239.5	1
3	78	12	305	1.63	41.4	8	630	285.8	1
4	103	(Close) 2⅞	73	1.73	43.9	8	180	81.6	1
4	103	4	102	1.73	43.9	8	285	129.3	1
4	103	5	127	1.73	43.9	8	380	172.4	1
4	103	6	152	1.73	43.9	8	440	199.6	1
4	103	8	203	1.73	43.9	8	600	272.2	1
4	103	10	254	1.73	43.9	8	775	351.5	1
4	103	12	305	1.73	43.9	8	925	419.6	1
5	129	(Close) 3	76	1.84	46.7	8	240	108.9	1
5	129	5	127	1.84	46.7	8	480	217.7	1
5	129	6	152	1.84	46.7	8	600	272.2	1
5	129	8	203	1.84	46.7	8	825	374.2	1
5	129	10	254	1.84	46.7	8	1055	478.5	1
5	129	12	305	1.84	46.7	8	1260	571.5	1
6	155	(Close) 3⅛	79	1.95	49.5	8	350	158.8	1
6	155	5	127	1.95	49.5	8	660	299.4	1
6	155	6	152	1.95	49.5	8	820	372.0	1
6	155	8	203	1.95	49.5	8	1125	510.3	1
6	155	10	254	1.95	49.5	8	1440	653.2	1
6	155	12	305	1.95	49.5	8	1720	780.2	1

Galvanized Rigid Conduit (GRC) Nipples

Listed to Safety Standard UL 6
Manufactured in accordance with ANSI C80.1



¹Minimum requirement as per UL Standard

