



Representative Image

## Catalog No. TL412CT

**Description:** MLO 125A 4CRT 1P3W 120/240V W/GRND

**UPC No** 783164209693

**Home > Load Centers > Single Phase - USA**

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL412CT features space for 4, 1" breakers, a 125 A bus ampere rating, a factory included ground bar, and a combination surface/flush enclosure.

### Descriptors

Category	Single Phase - USA
GO Schedule	RA

### Specifications

Input/Output Voltage	120/240V ac
Type	Factory Included Ground Bar
Interrupting Capacity Rating	10
Amperage	125 A
Device type	Main Lug
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	1 Phase
Socket Type	0
1" Space	4
1/2" Space	8
Feed	Either
Door	No
GSA Compliance	No
NEMA Rating	NEMA 1
Circuit Breaker Style	Plug-In

### Classifications

UL/CUL Listing	UL
----------------	----

## Publications

Title	Publication No.	Publication Type
<a href="#">Section 1 BuyLog: Load centers and circuit breakers</a> Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. <a href="#">Outline Drawing</a>	DET1023	Application and Technical
1 page outline drawing in pdf format.	10103091-SH49	Drawings-Outline and Dimensional

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.