



Search Parameters:

e-Catalog > Switches & Disconnects > Disconnect & Safety Switches

Switches & Disconnects, Disconnect & Safety Switches

Product #: TFN60R

Short Description: GNL DTY AC DISCONNECT

Print This Page
Email This Page

SPECIFICATIONS

Table with 2 columns: Specification Name (e.g., Category, Voltage, Amperage) and Value (e.g., Puller Type AC Disconnect, 240 Vac, 60A).



View Larger

Additional Resources for Puller Type AC Disconnect

Safety Switches Definite Purpose. Spec-Setter™ Safety Switches. Air Conditioner Disconnects. Puller type. UL Listed. Fusible – UL869. Service Equipment. No fuse – UL1429. Enclosed Pull-out Switch. Horse power rating: 10. Enclosure material: Steel. Standard Package: 6. Devices do not have removable closing cap.

Navigation menu with columns: Products, Services, Markets, Resources, Your Business, News & Events, Where To Buy. Each column contains a list of links to various GE resources and services.

Industrial Solutions section. Includes a paragraph about GE's role in electrification, a list of links (ABOUT US, CONTACT INFORMATION, PRIVACY, TERMS OF USE), and footer information including the Olympic logo, 'WORLDWIDE PARTNER', and copyright notice for 2013 General Electric.