



SKU: IK-4

UPC: 0783669470062

Features & Benefits:

Description: Copper Split Bolt, Conductor Range for Equal Main & Tap 4 Sol - 8 Sol, UL, CSA

Specs

Additional Class Attributes

| | |
|----------------------|------------|
| Connection | Mechanical |
| Number of Conductors | 1 |
| Number of Poles | 1 |

Conductor Ranges

| | |
|--|---------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | NA |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | NA |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range for Equal Run & Tap Str | 4 Str - 7 Str |
| Conductor Range for Equal Run & Tap Sol | 4 Sol - 8 Sol |
| Conductor Range for Minimum Tap with Maximum Run | 16 Sol |
| Conductor Range AL Solid (Primary, run, main, line) | NA |
| Max Conductor Copperweld - Str | 3 No. 12 |
| Max Conductor Copperweld - Type A | 8A |

Dimensions

| | |
|----------------------------------|---------------|
| Drive Size Main | 11/16 |
| Drive Type Main | External Hex |
| Height (IN) | 0.69 |
| Height BX (IN) | 2 |
| Length (IN) | 1.05 |
| Weight (LB) | 0.067 |
| Weight BX (LB) | 7.677 |
| Width (IN) | 0.79 |
| Width BX (IN) | 6.1875 |
| Wire Diameter Range Primary (IN) | 0.128 - 0.204 |

Material and Finish

| | |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish | NA |
| Insulation | NA |

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|--|-----|
| Number of Wire Binding Screws per Port | 1 |
| Wire Binding Screw Size | NA |
| Wire Binding Torque | 165 |

General

| | |
|-----------------------------|------------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 100 |
| Direct Burial | Yes |
| Dual Rated | No |
| NEMA Code | S-588-4 |
| UPC Code | 78366947006 |

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | LR-701570 |
| CSA Standard | C22.2 No. 65 |
| Prop65 Compliance | WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov |
| UL Control Number | 460C |
| UL / CULUS Specification | UL 467 Listed |
| UL File Number | E6207 |

Environment and Temperature

| | |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

Color

| | |
|-------|--------|
| Color | Copper |
|-------|--------|

Voltage

| | |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|