



SKU: ULT-6-Z

UPC: 0783669930795

Features & Benefits:

Description: Permagraund Copper Grounding C Crimp, Main Conductor Range 2 Str-2 Sol, Tap Range 4-8 Sol, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	ND-C

Dimensions

Height (IN)	0.83
Height BX (IN)	2
Length (IN)	0.99
Weight (LB)	0.084
Weight BX (LB)	8.547
Width (IN)	0.614
Width BX (IN)	6.1875
Width (mm)	15.5956

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366993079

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
Color Code	NA

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol
Conductor Range CU Solid (Secondary, tap, load)	4 Sol - 8 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2 Str
Conductor Range CU Stranded (Secondary, tap, load)	4 Str - 8 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------