## ERICO CADWELD ONE SHOT, Cable to Ground Rod – GT1162C







- Single use ceramic mold which eliminates the need for a graphite mold and handle clamp/frame
- Produces a permanent connection that will not loosen or corrode
- Fits plain copper-bonded, threaded copper-bonded, full-size galvanized and stainless steel ground rods
- NEC<sup>®</sup> compliant





| Part Number                  | GT1162C         |
|------------------------------|-----------------|
| Welding Material Type        | Traditional     |
| Mold Family                  | GT (ONE SHOT)   |
| Ground Rod Diameter, Nominal | 5/8"            |
| Ground Rod Diameter, Actual  | 0.555" – 0.635" |
| Connection, Solid            | 1/0<br>2/0      |
| Connection, Stranded         | #1<br>1/0       |
| Certifications               | cULus           |
| Standard Packaging Quantity  | 6 pc            |
| UPC                          | 78285600097     |

A gap between conductors may be required. See mold tag for more information.

NEC is a registered trademark of, and National Electrical Code (NEC) standard is a copyright of the National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



