



Product Data Sheet

94 Eagle Fork Rd Hayesville, NC 28904
Ph: 800.343.2579 Fax: 828.389.3922

Part Number: 981802
Description: 18 AWG solid bare copper Two Conductor, unshielded with Plenum jacket
Suitable Application: Power Limited Fire Alarm Signaling Cable

Construction Details:

Total Number Conductors	2
Conductor Material	18 AWG Solid Bare Copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.008"
Nominal Insulation Diameter	.056"
Color Code	Black, Red
Cabling Overall Lay	2.5" left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	Red
Nominal Jacket Diameter	.143"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Print Sample Generic Legend:

18 AWG 2C PLENUM FIRE ALARM CABLE (UL) TYPE CL3P OR FPLP OR c(UL)us TYPE CMP E179335

Electricals:

Voltage Rating:	300 volts
Temperature Rating:	-5°C to +75°C
Capacitance	37 pF/ft

Applicable Standards:

UL	FPLP, CL3P
c(UL)us	CMP
ROHS Compliant	Yes

Customer Name: _____ Date Signed: _____

Customer Approval: _____

Specification Issue Date: 9/28/07

Rev. 12/2/2020