

Specifications



Photo is representative

Eaton DH661UWK

Eaton Heavy duty single-throw non-fused safety switch, Single-throw, 30 A, NEMA 4X, Stainless steel, Non-Fusible, Six-pole, Six-wire, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc, 15 at 600 Vdc

General specifications

| | |
|-----------------------------|--|
| PRODUCT NAME | Eaton heavy duty non-fusible safety switch |
| CATALOG NUMBER | DH661UWK |
| UPC | 782113523392 |
| PRODUCT LENGTH/DEPTH | 10.22 in |
| PRODUCT HEIGHT | 19.08 in |
| PRODUCT WIDTH | 13.42 in |
| PRODUCT WEIGHT | 28 lb |
| WARRANTY | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| CERTIFICATIONS | UL Listed |
| CATALOG NOTES | 600V Vdc hp rating requires switch be wired per wiring diagram on device publication |



Powering Business Worldwide

Physical Attributes

| | |
|---------------------------|-----------------|
| ENCLOSURE | NEMA 4X |
| ENCLOSURE MATERIAL | Stainless steel |
| FUSE CONFIGURATION | Non-fusible |
| NUMBER OF POLES | Six-pole |
| NUMBER OF WIRES | 6 |
| TYPE | Single-throw |

Miscellaneous

| | |
|-------------------------|--|
| PRODUCT CATEGORY | Heavy Duty 6-Pole Motor Circuit Safety Switch |
|-------------------------|--|

Performance Ratings

| | |
|------------------------|---|
| AMPERAGE RATING | 30A |
| HP RATING - MAX | 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc, 15 at 600 Vdc |
| NEMA RATING | NEMA 4X |
| VOLTAGE RATING | 600 V |

Resources

| | |
|--|---|
| CATALOGS | Commercial Distribution, Switching Devices, Volume 2, Tab 1 |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - DH661UWK |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

