



Buck-Boost Transformer - Single Phase, 120 X 240 - 16/32V

By Acme Electric
Catalog # [B1003K0290C](#)

Low Voltage Buck-Boost Transformer - Single Phase, 120 X 240 - 16/32V, 3kVA



Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

Specifications

Nema Rating	NEMA 3R
UL Standard	UL 506
CSA Standard	C22.2 No 47
Buy American Compliant	Contact Manufacturer
UL Insulation Class	200°C

Current

Frequency Rating	60 Hz
Primary Voltage	120 X 240 V
kVA	3.0
Secondary Voltage	16/32 V

Dimensions

Weight	66.2 lb.
Height	13.07 in
Width	6.81 in

Length	7.75 in
Dimensions	7.75 in x 6.81 in x 13.07 in

General

Product Type	Buck-Boost Transformer
Material type	ZFIN
Mounting Type	Wall
Product Family	Single Phase Buck-Boost
UPC	047503072653
Winding Material	AL
Construction	Encapsulated

Logistics

Pallet Quantity	6
Carton Quantity	1

Operational

Max Temperature Rise	135 Degrees Celsius
----------------------	---------------------

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)