



Specification Sheet

600V Class Commercial Potted Distribution Transformer

HPS Fortress™

- Phase** Available in single phase and three phase
- Winding Material** Aluminum
- Rating** Single Phase ratings from 50VA to 37.5kVA, Three Phase ratings from 2kVA to 75kVA
- Voltage** Primary volts: 120 x 240, 208 x 416, 120/208/240/277, 240 x 480, 277, 277/480, 347/380, 600
Export model available.
- Frequency** 60 Hz frequency (50/60 Hz on four single phase voltage groups)
- Insulation System** 130°C/180°C
- Core** All welded core construction made with high quality, high permeability silicon steel laminations
- Coil** Copper or aluminum windings, with terminations brazed, welded or bolted.
- Termination** Front accessible wiring compartment with high and low voltage lead wires or copper tabs.
- Enclosure** Heavy Duty Type 3R (Conduit knockouts on sides and rear). Encapsulated with electrical grade silica sand and resin compounds.
- Mounting** Wall mounting up to 45 kVA and floor mounting for all three phase units above 15 kVA.
- Warranty** 10 year

Approvals and Standards



CSA Certified, UL Listed

Features and Benefits

Electrostatic shield standard on all three phase units and single phase units from 750VA and up

Electrostatic Shielding on all single phase units over 0.50 kVA

Options

Custom sizes, ratings and styles available upon request

Type 4/12 gasketing kit.

Stainless Steel Nameplate

Data subject to change without notice. Please visit www.hammondpowersolutions.com for the most current data.