



**SKU:** NBST-2/0

**UPC:** 0783669204360

**Features & Benefits:**

**Description:** Aluminum Neutral Bar Adapter, Conductor Range 2/0-14, Tin Plated, UL

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	NA
Number of Conductors	1
Number of Poles	1
Number of Ports Tap	1
Replacement Part(s)	NA

### Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	0.78
Height (mm)	19.812
Length (IN)	1.14
Length (mm)	28.956
Tang Length (IN)	0.44
Tang Length (mm)	11.176
Tang Thickness (IN)	0.16
Tang Thickness (mm)	4.064
Tang Width (IN)	0.46
Tang Width (mm)	11.684
Weight (LB)	0.021
Width (IN)	0.7
Width (mm)	17.78

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366920436

### Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

### Color

Color	Silver
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol