

Project Name

Location

Prepared By



SATCO S11758

40T8L/96/8CCT5/B/CF/U

Notes

(revised) 10-22-2023 09:20:07

General

Status	Active
Watts	24W/32W/40W
Fluorescent Equivalent	59W/86W/96W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	3500L/4400L/5500L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	T8
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	93.88
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.88

Additional Information

Includes	(1) Set R17d & Fa8 Endcaps
Shatter-Proof Type	PET Coated
Specification Note	Not for use in fully enclosed vapor tight fixtures
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cRUus; cULus
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-3Y6HM9
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
NSF Approved	Yes
Flicker Free	No
SDS Sheet	LED_Lamp