

SECURITY ALARM CABLE | PLENUM SHIELDED



AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	SOL	982202SD	60	.015	.38	.114	2.90	13
	2	7	912202SD	59	.015	.38	.120	3.05	13
	3	7	912203SD	59	.015	.38	.127	3.23	17
	4	SOL	982204SD	59	.018	.46	.126	3.20	20
	4	7	912204SD	59	.015	.38	.138	3.51	20
	6	7	912206SD	59	.015	.38	.163	4.14	26
	8	7	912208SD	59	.015	.38	.173	4.39	32
	10	7	912210SD	59	.015	.38	.190	4.83	38
	12	7	912212SD	59	.015	.38	.205	5.21	46
20	2	7	912002SD	62	.015	.38	.139	3.53	19
	3	7	912003SD	62	.015	.38	.148	3.76	22
	4	7	912004SD	62	.015	.38	.161	4.09	27
18	2	7	911802SD	65	.015	.38	.162	4.11	23
	3	7	911803SD	65	.015	.38	.175	4.45	30
	4	7	911804SD	65	.015	.38	.191	4.85	37
	6	7	911806SD	65	.015	.38	.229	5.82	51
	8	7	911808SD	65	.015	.38	.241	6.12	66
	9	7	911809SD	65	.015	.38	.254	6.45	73
16	2	7	911810SD	65	.015	.38	.266	6.76	78
	12	7	911812SD	65	.015	.38	.289	7.34	94
	2	19	911602SD	73	.015	.38	.187	4.75	30
14	3	19	911603SD	73	.015	.38	.198	5.03	39
	4	19	911604SD	73	.015	.38	.218	5.54	49
12	2	19	911402SD	75	.015	.38	.229	5.82	45
	3	19	911403SD	75	.015	.38	.246	6.25	60
	4	19	911404SD	75	.015	.38	.264	6.71	78
12	2	19	911202SD	84	.015	.38	.263	6.68	63
	4	19	911204SD	84	.015	.38	.316	8.03	110

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0419



(800) 343 2579 • www.adcable.com

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted, aluminum mylar shielding with drain wire and an overall low smoke white PVC jacket* with rip cord.

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

SPECIFICATIONS

Conductor Bare Copper

Insulation Low Smoke PVC

- 22 AWG .007" PVC
- 20 AWG .008" PVC
- 18 AWG .009" PVC
- 16 AWG .010" PVC
- 14-12 AWG .012" PVC

Shield Aluminum Mylar

Jacket Low Smoke PVC

NEC Articles

- 22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P

Voltage Rating 300 V

Temp. Rating -25°C to 75°C

Drain Wire

- 24 AWG Tinned Copper

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC SHIELDED (UL)
TYPE CL3P/FPLP c(UL)us TYPE
CMP E179335

*14-12 AWG are not recognized by c(UL) or c(ETL).

*Other colors available upon request. Please consult factory for minimums and lead times.