



Motor Start Capacitors 220/250 VAC



- Dry Electrolytic Non Polarized Capacitor
- -40 to 70 Degrees Celsius Rating
- Rated for 3 Second Start
- 20 Starts per Hour
- 220-250 VAC
- UL and cUL Recognized



CAT. NO.	PRIOR CAT#	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TTMJ21	35-21A250*	21-25	1-7/16"	2-3/4"	100
TTMJ25	35-25A250*	25-30	1-7/16"	2-3/4"	100
TTMJ30	35-30A250*	30-36	1-7/16"	2-3/4"	100
TTMJ36	35-36B250*	36-43	1-7/16"	2-3/4"	100
TTMJ43	35-43B250*	43-53	1-7/16"	2-3/4"	50
TTMJ53	35-53A250*	53-64	1-7/16"	3-3/8"	100
TTMJ64	35-64A250*	64-77	1-7/16"	2-3/4"	100
TTMJ72	35-72D250*	72-88	1-13/16"	3-3/8"	50
TTMJ88	35-88D250*	88-108	1-13/16"	3-3/8"	50
TTMJ108	35-108D250*	108-130	1-13/16"	3-3/8"	50
TTMJ124	35-124D250*	124-149	1-13/16"	4-3/8"	50
TTMJ145	35-145F250*	145-174	1-13/16"	3-3/8"	50
TTMJ189	35-189G250*	189-227	2-1/16"	4-3/8"	50
TTMJ216	35-216F250*	216-259	2-1/16"	3-3/8"	50
TTMJ243	35-243G250*	243-292	2-1/16"	3-3/8"	50
TTMJ270	35-270G250*	270-324	2-1/16"	3-3/8"	50
TTMJ320	35-320H250*	320-384	2-1/16"	4-3/8"	50
TTMJ378	35-378H250*	378-455	2-9/16"	4-3/8"	50
TTMJ400	35-400H250*	400-480	2-1/16"	4-3/8"	50

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST