

## Cable Adapter with Cable Insulation Diameter Range = 1.370 - 1.630 inches

By Hubbell Power Systems  
Catalog # [625CAM](#)



15/25/28 kV 600/900 Amp Cable Adapter, Cable Insulation  
Diameter Range = 1.370 - 1.630 inches

### Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Tapered design

### General

Catalog Number	625CAM
EU RoHS Indicator	No
Type	600 Amp Dead Break
UPC	096359393122

### Dimensions

Cable Insulation Diameter Maximum	1.63 in
Cable Insulation Diameter Minimum	1.37 in
Weight	1 lb

### Electrical Ratings

AC Withstand Voltage (1 min)	45 kV
------------------------------	-------

Basic Impulse Level	125 kV
Corona Extinction (3pC)	21 kV
Current Rating	600 A
Voltage Rating	15 kV

### Conductor Related

Cable Insulation Diameter Range	1.370 - 1.630
------------------------------------	---------------

### Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	--

### Logistics

Pallet Quantity	1536
Standard Package	1

### Product Assets

- [Catalogs - Cable Accessories](#)
- [Sales Drawings - 625CA](#)
- [SDS - VERSILUBE G661 SILICONE COMPOUND](#)
- [Specifications - 625CAM](#)
- [Video - Grease Best PRactices](#)