

Project:	Туре:
Prepared By:	Date:

Driver Info)	LED Info	
Туре	Constant Current	Watts	38W
120V	N/A	Color Temp	3000K/4000K/5000K
208V	N/A	Color	Color 90 CRI
240V	N/A	Accuracy	, o e
277V	N/A	L70 Lifespan	15,000 Hours
Input Watts	38W	Lumens	3,600 lm
•		Efficacy	95

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations

Electrical

Voltage:

120-277VAC, 60Hz

Power Consumption:

4W

Surge Protection:

Withstands up to 6000 volts

Switching Capacity:

600W @ 120VAC Electronic Ballast (LED) 1350W @ 277VAC Electronic Ballast (LED)

Wall Switch Manual Override:

Two flip logic prevents activation by momentary power outages. Stays on for 6 hours. No extra wiring needed.

Sensor Specifications

Time Adjustment:

5 seconds to 15 minutes

Detector Sensitivity:

Adjustable from 50%% to 100%

Sensor Housing:

Made of tough, corrosion resistant polycarbonate

Detection:

110° view

Other

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Lamp Warranty:


RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

GT500RW/L





Features

Two CCT-Selectable PAR38s

110° view sensor

6 Hour protected manual override

EZ Plate Universal cover fits all boxes

Ordering Matrix

Family	Detection	Flood Type	Finish	Lamps/Wattages/CCT
GT	500	R	W	/L

500 = 110° View **R** = 120V R90 Flood **Blank** = Black **/L** = 2-Edison Base PAR38 Lamps, 38W, Selectable CCT: 3000/4000/5000K **W** = White