



SKU: ACON-750

UPC: 0783669021509

Features & Benefits:

Description: Aluminum Compression Pigtail Adaptor offset, Conductor size 750, Tin Plated, cULus

Specs

Dimensions

Height BX (IN)	2
Weight BX (LB)	1.427
Width BX (IN)	6.1875

Additional Class Attributes

Barrel Marking	Ink
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	936
Number of Conductors	1

Material and Finish

Conductor Material	Copper/Aluminum
Connector Finish	Tin
Insulation	Supplied with insulating cover
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366902150

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -

www.P65warnings.ca.gov

UL Control Number

941R

UL / CULUS Specification

UL/cUL 486A/B Listed

UL File Number

E62542

Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Yellow

Voltage

Voltage Rating

600 V

Voltage Rating without cover

35 kV

Conductor Ranges

Approximate Pin Size

500 kcmil