



# 3303-NK



## Product Description

Three gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 3303-NK

**Carton Quantity:** 20  
**Carton Weight:** 18 lb.

**Height:** 3-3/4 in.  
**Width:** 5-11/16 in.  
**Depth:** 3-9/16 in.  
**Volume:** 56.5 cu. in.  
**Type of Installation:** New Work  
**Wall Box**  
**Number of Gangs:** 3

**UPC:** 085339152019  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

## FEATURES

Machine tapped device holes, slot provision for low voltage divider, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## STANDARDS

ANSI / UL 514C: File No. E30594



## APPLICATION

New work residential construction 2 HR fire resistive walls

## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

## COLOR

Beige/tan

## ADDITIONAL MATERIALS

Carbon steel fasteners

## MATERIAL

Fiberglass reinforced polyester BMC

Polyvinyl chloride clamps

## MOUNTING

Angled mid nails