



Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V

By Acme Electric
Catalog # [B1500V0280C](#)

Low Voltage Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V, 500VA



Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

Specifications

Nema Rating	NEMA 3R
UL Standard	UL 506
CSA Standard	C22.2 No 47
Buy American Compliant	Contact Manufacturer
UL Insulation Class	200°C

Current

Frequency Rating	60 Hz
Primary Voltage	120 X 240 V
kVA	0.50
Secondary Voltage	12/24 V

Dimensions

Weight	15.5 lb.
Height	8.5 in
Width	4.6 in

Length	5.1 in
Dimensions	5.1 in x 4.6 in x 8.5 in

General

Product Type	Buck-Boost Transformer
Material type	ZFIN
Mounting Type	Wall
Product Family	Single Phase Buck-Boost
UPC	047503073650
Winding Material	AL
Construction	Encapsulated

Logistics

Pallet Quantity	6
Carton Quantity	1

Operational

Max Temperature Rise	135 Degrees Celsius
----------------------	---------------------

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)