

912002

Part Number:

## PRODUCT DATA SHEET

94 Eagle Fork Rd Hayesville, NC 28904 Ph: 800.343.2579 Fax: 828.389.3922

Description:	20 AWG two conductor with a white plenum rated PVC jacket.		
Suitable Application:	Sound, Audio, Security, and Data Communication		
Construction Details:			
Total Number Conductors Conductor Material Insulation Material Insulation Thickness Nominal Diameter over Insulation Color Code Cabling Overall Lay Final Jacket Material Nominal Thickness Jacket Color Nominal Diameter over Jacket Ripcord	2 20 AWG 7-Strand Bare Copp Low smoke copolymer .008" .052" Black/Red 2.50" left hand lay Low smoke copolymer .015" White .135" Yes	er	
Print (Surface)			
Inkjet Sequential Foot Marks	Yes Yes		
Print Legend:			
20 AWG 2C (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E179335			
Electricals:		Applicable Standards:	
Voltage Rating: Capacitance CDR Temp Rating:	300 Volts 23 pF/ft -4C to +75C	UL Type	CMP, FPLP, CL3P
	40 10 1700	ROHS Compliant	Yes
Customer Name:	Date Signed:		
Customer Approval:			
Specification Issue Date: 8/20/15; Rev. 09/10/2020			