



**SKU:** TA-250

**UPC:** 0783669889420

**Features & Benefits:**

**Description:** Aluminum Mechanical Lug, Conductor Range 250-6, 1 Port, 1 Hole, 5/16in Bolt Size, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

### Dimensions

Dimension G (IN)	0.453
Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.122
Height BX (IN)	2
Height (mm)	28.4988
Length (IN)	1.984
Length (mm)	50.3936
Mounting Hole Diameter (IN)	0.328
Mounting Hole Spacing (mm)	0
Tang Length (IN)	0.992
Tang Thickness (IN)	0.25
Tang Width (IN)	0.99
Weight (LB)	0.266
Weight BX (LB)	4.3638
Width (IN)	0.99
Width BX (IN)	6.1875
Width (mm)	25.146

### Material and Finish

Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type

Stranded

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/16
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	11/16
Wire Binding Torque	275

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366988942

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
-------	--------

### Voltage

Voltage Rating	35 kV
----------------	-------