## OTHER MOUNTINGS



A wide variety of mounting accessories make Cablofil the easiest brand of Cable Management to install on the market. Every accessory has been designed to keep cables safe and create a durable installation.





61 C50CC

CONDUIT CLAMP KIT

61 CC KIT

CONDUIT CLAMP KIT

62 CE40CC & CH

CONDUIT ATTACHMENT FITTINGS & CONDUIT CLAMP KIT

63 FASCLM KIT BEAM CLAMP

3 ETC

TRAY BEAM SUPPORT

63 EZBC

**BEAM CLAMP** 

64 C 50

**ELECTRICAL BOX SUPPORT** 

64 SBDA

CONDUIT AND BOX SUPPORT

64 CM50I

INDUSTRIAL BOX
MOUNTING BRACKET

65 PLEXO3KIT/ PLEXO4KIT

TWIST-ON PLASTIC JUNCTION BOXES

55 TC4KIT/TC5KIT

TWIST-ON METALLIC JUNCTION BOXES

66 HB 2 KIT

WALL/FLOOR TERMINATION BRACKET

66 AB225 KIT

ANGLE BRACKET

7 CCLMP

**CABLE CLAMP** 

57 WMC2LA

TRAY-TO-LADDER CLAMP

67 DO

WATERFALL DROPOUT

68 CABLEXIT

58 DROP OUT KIT

CABLE DROP OUT KIT

68 YCKIT

YOKE CLAMP KIT

69 MFM

METALLIC MULTIFIX PLATE

69 CLIP

CABLE LABEL CLIP

69 CABLO SNAP

CABLE BUNDLER

70 EZVC

VELCRO ROLL

70 EZJB 5/16

J-BOLT

70 RB112KIT

RACK BRACKET KIT

71 SZMCKIT

SEISMIC BRACING KIT

71 SZMCCUTR

CABLE CUTTER

71 SZMCSWAG

HAND SWAGER

72 FS 41

**FASTRUT CONNECTOR** 

2 GNDSB

GROUNDING LUG

72 GNDCL

**GROUNDING LUG** 

73 FAS ROLLER

74 FAS ROLLER HD

HEAVY DUTY

75 CABLO-PORT ROOF TOP SUPPORTS

82 FLAMESTOPPER


60



## FS 41 FASTRUT CONNECTOR







- FASTRUT attaches tray to strut without bolts and nuts or tools.
- Reduces installation time.
- Install FASTRUT on outer wires of tray, and both sides of the strut.
- 2 required for tray 12" or smaller.
- 3 required for tray 18" or larger.

	PKG. QTY.	WEIGHT		DC	316L	BL	PE
		LBS	KG				
FS 41	50	3.3	1.5	599 007	599 004	942 823	942 824

## GNDSB GROUNDING LUG



- Accommodates AWG 3-14 grounding wires.
- Use one GNDSB every 60' and/or at the end of each tray run. If tray is used as an Equipment Grounding Conductor, use one on each section of tray for a code compliant installation.
- Works with any size Cablofil tray.
- UL Listed, CSA Approved.

	WEI	GHT	CU*
	LBS	KG	(I)
GNDSB	0.07	0.03	942 616

\*CU= Copper

## **GNDCL**GROUNDING LUG





- Accommodates AWG 1/0 #6 grounding wires.
- Use one GNDCL every 60' and/or at the end of each tray run. If tray is used as an Equipment Grounding Conductor, use one on each section of tray for a code compliant installation.
- Works with any size Cablofil tray.
- UL Listed, CSA approved.
- Tin-plated

	WEIGHT		CU*
	LBS	KG	(I)
GNDCL	0.2	0.1	942 866

\*CU= Copper