


SKU: ASL-750

UPC: 0783669010190

Features & Benefits:

Description: Aluminum Stacking Adapter, Conductor Range 1/0-750, Tin Plated, UL



Specs

Additional Class Attributes

Barrel Marking	Hard
Flared End	No
Mounting Method	Bolted
Number of Mounting Holes	2
Sight Window	No
Slotted	No

Dimensions

Height (IN)	1.25
Height BX (IN)	2
Length (IN)	3
Max Insulation OD (IN)	1.372
Weight (LB)	0.2287
Weight BX (LB)	2.434
Width (IN)	1
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	0-000-1
UPC Code	78366901019

Bolt and Screw Sizes

Mounting Bolt/Stud Size 1/2 to 5/8

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating 90°C

Color

Color Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 1/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 1/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating 35 kV