

Furnace Blower Motors

Direct Drive



**BALL BEARINGS
NOW STANDARD**

Features:

- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Uses 370V Capacitors
- Standard 48 Frame Motor Casing Size
- 2.5" Diameter Hub Rings included
- Low Power Consumption
- Automatic Thermal Overload Protector
- Continuous Duty, Air Over
- Electrically Reversible
- Class B Insulation
- Speed: 1075/3
- Quiet Operation
- 60 HZ
- cURus Listed
- Shaft Diameter 1/2"

CAT. NO.	HP	VOLTAGE	SPEED	FLA	UOM	ORDER MULTIPLE
TWG840583	1/4	115	1075/3	4.6	EA	1
TWG840584	1/4	208-230	1075/3	2.2	EA	1
TWG840585	1/3	115	1075/3	6.7	EA	1
TWG840586	1/3	208-230	1075/3	2.9	EA	1
TWG840587	1/2	115	1075/3	10.2	EA	1
TWG840588	1/2	208-230	1075/3	5.0	EA	1
TWG840589	3/4	115	1075/3	11.3	EA	1
TWG840590	3/4	208-230	1075/3	5.4	EA	1
TWG840595	1	115	1075/3	12.6	EA	1
TWG840596	1	208-230	1075/3	5.59	EA	1