

**GALVANIZED** 

257 06/22/2015 DATE

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE

4-11/16" SQUARE WELDED BOX 2-1/8" **DEEP WITH RAISED GROUND. SOLID** PIGTAIL, STUD BRACKET, AND FARSIDE **SUPPORT** 

SUBJECT TO CHANGE WITHOUT NOTICE

TOLERANCE UNLESS OTHERWISE SPECIFIED

**INITIAL RELEASE** 

SYM. REVISION DESCRIPTION

.XX DECIMAL ±.015 .XXX DECIMAL ± .005 ANGLE ±2°

South Bend, Indiana J.R. DRAWN BY: APP. BY:

J.R. APP

SCALE: N.S. 1:3 06/22/2015 DATE:

**LIST OF PARTS** (FARSIDE SUPPORT)) DESCRIPTION **MATERIAL** (PIGTAIL) **SPACER** STEEL Ù.L. LISTÉD 600 VOLT MAXIMUM. SIDE STEEL NO. 12 AWG GREEN TW **INSULATED SOLID FASTENERS** STEEL COPPER WIRE CUT 8-1/2" LONG **FARSIDE** IN FLAT. **STEEL** SUPPORT STRIPPÉD 1" IN FROM EACH END WITH #10-32 X 3/8" GROUND **INSULATED PIGTAIL** SOLID COPPER SCREW W/ COMBO HEX WASHER HEAD (SLOTTED, STUD BRACKET STEEL #2 PHILLIPS AND ROBERTSON) A (SPACER)

2.45 [62.3]	2.75 [69.9]	(E (SIDE))
4.25 (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c		4.73 [120.1]
2.13 [54] INSIDE	5.60 [142.3]	8-32 X 1/2" PHIILPS / SLOT DRIVE (FASTENER)
2.24 [56.9]  .31 [7.9]  (D (SPACER))		ADJUSTABLE 2-1/2" [63.5] 3-1/2" [89] 3-5/8" [92] 4" [101.6]

(STUD BRACKET) 4.69

119.1

**NOTE:** FOR INSTRUCTION SHEET SCROLL DOWN TO NEXT SHEET 6" NOTES:

1. ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS]

B (SPACER)

2. BOX VOLUME: 42 IN3 [688.2 CM3]

ACCEPTS ALL 4-11/16" COVERS,707RAC & 709 3. PARTITIONS, ALL SOLD SEPARATELY

4. **ULLISTED** 

5. KNOCKOUTS IN LOCATION "A" ARE ACCESSIBLE FOR 5-1/2" [140] & 6" [152.4] STUDS ONLY

KNOCKOUTS			
TRADE SIZE	LOCATION	QTY.	
(1/2"-3/4") TKO®	B, C, D, E	3	
(1/2"-3/4") TKO®	A (SEE NOTE 5)	3	
1/2" KO	A (SEE NOTE 5)	1	

5-1/2" [140]

[152.4]

Ì

SIZE:

## Instructions for using the RACO® Universal Box Stabilizer


## 1-1/2" Deep Boxes

## 2-1/8" Deep Boxes




Bend center tab as shown

For 2-1/2" deep studs




Comes preset



Bend center tab as shown - 2 places

For 3-1/2" deep studs



Bend center tab as shown - 2 places




Bend center tab as shown

For 3-5/8" deep studs



Bend center tab as shown



Bend center tab as shown

For 4" deep studs



Bend center tab as shown



Bend both tabs as shown

For 5-1/2" deep studs



Bend both tabs as shown



Bend both tabs as shown

For 6" deep studs



Bend both tabs as shown

NOTICE: Bottom knockouts are NOT usable with the FS support.