



## Catalog No. TH3365

**Description: 400A 3P HD N1 600V FUSIBLE**

**UPC No 783164009170**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH3365



Representative Image

### Descriptors

|             |            |
|-------------|------------|
| Category    | Heavy Duty |
| GO Schedule | S1         |

### Specifications

|                           |                          |
|---------------------------|--------------------------|
| Voltage                   | 600 AC                   |
| Amperage                  | 400 A                    |
| Poles                     | 3                        |
| Wires                     | 3                        |
| Fusing                    | Fusible                  |
| Enclosure                 | NEMA 1 (Indoor)          |
| Options                   | None                     |
| Wire Range (Cu/Al)        | (1) 2-600 or (2) 1/0-250 |
| 240 Vac, NEC Std, 3-ph    | 50.0 hp                  |
| 240 Vac, Time Delay, 3-ph | 125.0 hp                 |
| 480 Vac, NEC Std, 3-ph    | 100.0 hp                 |
| 480 Vac, Time Delay, 3-ph | 250.0 hp                 |
| 600 Vac, NEC Std, 3-ph    | 125.0 hp                 |
| 600 Vac, Time Delay, 3-ph | 350.0 hp                 |
| 250 Vdc                   | 50.0 hp                  |
| GSA Compliance            | Yes                      |

### Classifications

|               |     |
|---------------|-----|
| CSA Certified | Yes |
| UL Listed     | Yes |

### Dimensions

|        |          |
|--------|----------|
| Height | 53.9 in  |
| Depth  | 8.3 in   |
| Width  | 22.9 in  |
| Weight | 126.0 lb |

**by ABB**

## Dimensions

|        |          |
|--------|----------|
| Height | 53.9 in  |
| Depth  | 8.3 in   |
| Width  | 22.9 in  |
| Weight | 126.0 lb |

## Publications

| Title  | Publication No. | Publication Type                 |
|--|-----------------|----------------------------------|
| 600A - Safety Switches<br>1 page outline drawing in .pdf format. | 10103091-SH112  | Drawings-Outline and Dimensional |

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.