



**SKU:** PCT-6-600

**UPC:** 0783669700688

**Features & Benefits:**

**Description:** Cleartap Insulated Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 600-2, 6 Ports, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	6
Number of Poles	1
Number of Ports / Wireways	6
Number of Usable Ports	6

### Dimensions

Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	3.115
Height BX (IN)	6.5
Height (mm)	79.121
Length (IN)	8.372
Length (mm)	212.6488
Max Insulation OD (IN)	1.172
Max Insulation OD (mm)	29.7688
Weight (LB)	2.37
Weight BX (LB)	7.8127
Width (IN)	3.147
Width BX (IN)	12.75
Width (mm)	79.9338

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	13/16
Wire Binding Torque	375

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366970068

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

## Color

Color	Clear
-------	-------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	600 kcmil - 4 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	600 kcmil - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	NA

## Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	475 Amps
Conductor Type	Stranded

## Voltage

Voltage Rating	600 V
----------------	-------

## Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C