NUD-88 Series

LEDUR 120V Edge-Lit Under Cabinet

Source: 7W

360lm per foot

| Гуре | | |
|-------------|--|--|
| Project | | |
| Catalog No. | | |
| Notes | | |

PRODUCT DESCRIPTION

LEDUR LED undercabinet uses edge-lit placement of diodes to give a Uniform Reflectance of light. The LEDUR produces an even 360 lumens/7 watts average per foot. Dimmable, no UV and forward heat make LEDUR the perfect energy saving lighting solution in undercabinet and shelf lighting. The LEDUR's uniform reflectance is excellent when used undercabinet over granite, polished stone or any reflective surface, additionally it is excellent in retail display lighting where diode image might distract from display merchandise.

FEATURES

- · Edge-lit design eliminates LED diode image
- · 2700K, 3000K or 4000K @ 90+ CRI
- 360 Lumens/ 7 watts per foot average
- Available in 6 different lengths; 8-3/4", 11-1/4", 18-1/4", 22-1/4", 32-3/4" & 42"
- Available in Dark Bronze or White Finish
- · Built-in on/off rocker switch
- · Linkable up to 400 Watts fixtures
- · 3 wire grounded electrical port on both ends for power or linking
- · Quick connect stab-in connectors included
- · Captive Screws for easy moutning
- · Integral electronic dimmable driver

ELECTRICAL

Input Voltage: 120V Lumens / Wattage:

8" = 242lm / 4.5W; **11"** = 337lm / 6.7W; **18"** = 608lm / 11W; **22"** = 646lm / 12W; **32"** = 1006lm / 16W; **42"** = 1456lm / 20W

Color Temperature: 2700K, 3000K or 4000K

CRI: 90+CRI

Maximum Run Length: 400W Dimming: Triac or ELV

Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.

CONSTRUCTION

Housing: Rear wireway access cover with stab-in electrical connectors facilitate wiring without opening the fixture. Additional knock-outs for top and back wiring.

Installation: Mounting hardware is included with each unit. Captive screws allow for quick installation, simply wire using rear door and quick connects, and hold in place and drive captive screws into material. Captives screws are covered with an included cap for a beautiful finished look.

Included with every fixture: Mounting Hardware and 1/2" die-cast metallic cable clamp, end to end connector and installed On/Off rocker switch.

LABELS AND LISTINGS

- · cULus Listed for Dry Location
- · ENERGY STAR® Certified
- · 5-Year Limited Warranty
- Can be used to comply with 2016 Title 24 part 6 High Efficacy LED light source requirements










PRODUCT IMAGES AND DIMENSIONS



Captive Screws for easy mounting located at each end under removable cap



LEDUR 120V Edge-Lit Under Cabinet

| Series | Length / Lumens / Wattage | CCT | Finish |
|--------|---|--|---|
| NUD-88 | 08 = 8" / 242lm / 4.5W 11 = 11" / 337lm / 6.7W 18 = 18" / 608lm / 11W 22 = 22" / 646lm 12W 32 = 32" / 1006lm / 16W 42 = 42" / 1456lm / 20W | /27 = 2700K /30 = 3000K /40 = 4000K* | BZ = Bronze WH = White |
| | | | |

st 4000K available in white finish only

Example: NUD-8822/30WH = 22" LEDUR 120V Edge-Lit Under Cabinet, 3000K, White Finish



NUD-88 Accessories

LEDUR 120V Edge-Lit Under Cabinet

Source: 7W

380lm per foot

Type
Project
Catalog No.
Notes



Junction Box

NUA-802B Black NUA-802W White

Used to power NUD-88 series using Jumper Cables or NUA-804 Hardwire Connector.

Finish: Black or White



End to End Connector

NUA-803

Used to join two NUD-88 fixtures seamlessly together. 3-wire grounded connector. Finish: White



72" 3-Wire Grounded Hardwire Connector

NUA-804B Black NUA-804W White

Used to hardwire NUD-88 fixtures to NUA-802 or junction box (by others). Finish: Black or White



72" Cord & Plug

NUA-805B Black NUA-805W White Convert NUD-88 series fixtures from

hardwire to direct plug-in units.
Finish: Black or White



Jumper Cable

NUA-806B 6" Black NUA-806W 6" White NUA-812B 12" Black NUA-812W 12" White NUA-824B 24" Black NUA-824W 24" White NUA-872B 72" Black NUA-872W 72" White Used to join NUD-88 fixtures together or



to NUA-802. Finish: Black or White

NORA