



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

**Search Parameters:**

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TGN3322R

Short Description: 60A 3P GD SS N3R 240V NONFUSE SW.

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	General Duty
Voltage	240 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 3R (Outdoor)
Options	None
Notes	Not suitable for use as service equipment
Height	13.68 in
Depth	3.88 in
Width	8.38 in
Weight	10.0 lb
Wire Range (Cu/Al)	12-2
240 Vac, NEC Std, 1-ph	10 hp
240 Vac, NEC Std, 3-ph	15 hp
250 Vdc	3 hp
600 Vdc	10 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131A
List Price	\$286



[View Larger](#)

**Publications/Resources**

[TGN3322R](#)

**Additional Resources for General Duty**

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-6](#)

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

