



PRODUCT DATA SHEET

94 Eagle Fork Rd Hayesville, NC 28904
 Ph: 800.343.2579 Fax: 828.389.3922

Part Number:	81402
Description:	14 AWG Solid Bare Copper 2 Conductor Riser Rated
Suitable Application(s):	Fire Alarm Cable

Construction Details:

Total Number of Conductors	2
Conductor Material	14 AWG Solid Bare Copper
Insulation Material	Polyvinyl Chloride
Insulation Thickness	0.012"
Conductor Insulation Color	Black, Red
Nominal Diameter over Insulation	0.088"
Cabling Overall Lay Length	4.00 Left Hand Lay
Final Jacket Material	Polyvinyl Chloride
Final Jacket Thickness	0.015"
Final Jacket Color	Red (Other Colors Available)
Nominal Diameter over Final Jacket	0.206"
Ripcord	Yes

Print Details:

Type: Inkjet
 Sequential Foot Markings: Yes

Sample Print Legend:

14 AWG 2C RISER FIRE ALARM CABLE (UL) TYPE CL3R OR FPLR E179335

Applicable Standards and Ratings	
Voltage Rating	300 Volts
Temperature Rating	-25°C to +75°C
UL Type(s)	UL 13 (CL3R), UL 1424 (FPLR)
ROHS Compliant	Yes
Nominal Capacitance	35 pF/ft
Max CDR DC Resistance @ 20 °C	2.57 Ω/1000 ft.

Customer Approval Signature: _____
Customer Name: _____
Specification Issue Date: 12/13/2021; Rev. 08/16/2022

Date: _____