



PRODUCT DATA SHEET

94 Eagle Fork Rd Hayesville, NC 28904
 Ph: 800.343.2579 Fax: 828.389.3922

Part Number: 71802SD
Description: 18 AWG 2C tinned copper Shielded Plenum CMP
Suitable Application: Temperature Control Cable

Construction Details:

Total Number Conductors 2
 Conductor Material 18 AWG 19-strand tinned copper
 Insulation Material Foamed FEP
 Insulation Thickness .013"
 Nominal Insulation Diameter .072"
 Color Code Black/White
 Cabling Overall Lay 3 " left hand lay
 Tape Material Low Smoke Foil Shield
 Drain Wire Material 24 AWG stranded tinned copper
 Final Jacket Material Low Smoke PVC
 Nominal Thickness .015"
 Jacket Color Purple (other colors available upon request)
 Nominal Jacket Diameter .178"
 Ripcord Yes

Print (Surface)

Inkjet Yes
 Sequential Foot Marks Yes
 (ascending/descending)

Print Legend:

18 AWG 2C SHLD "COMM 3 & COMM 4" 25pF/FT (UL) TYPE CL2P OR c(UL)us CMP E179334 MADE IN USA DEVICE / ZONE A B C D E 0 1 2
 3 4 5 6 7 8 9

Electricals

Impedance 58 Ohms/M'
 Capacitance 25 pF/ft.
 Voltage Rating 300 volts
 Temp. Rating -4C – +75C

Applicable Standards:

UL Type CL2P, CMP
 ROHS Compliant Yes

Customer Name: _____ Date Signed: _____

Customer Approval: _____

Specification Issue Date: 09/07/2011

Rev. 05/28/2020