

Bridgeport Fittings Inc.


705 Lordship Blvd. Stratford, CT 06615

Phone: 203-377-5944 Fax: 203-381-3488

Universal Clamp Straps

Images





Download Photo Image Download Dimensional Image

Dimension A in Inches: 4.20 Dimension B in Inches: 2.96 Dimension C in Inches: 1.20 Dimension D in Inches: 0.34

Application

The one piece clamp back and strap secures both cable and conduit. The UCS-150200 secures 1-1/2" and 2" EMT, Rigid, IMC, Metallic Liquid Tight, Nonmetallic Liquid DIA Dight, FMC, and Schedule 40 and Schedule 80 PVC conduit, as well as 1.735" Ø to 2.450" Ø steel and aluminum AC/MC cable. Plenum Rated for use in Air Handling systems, per UL 2043. Patent Pending

Product Information

Material: Zinc Plated Steel

Certifications & Codes:

Federal Specification Number: A-A-50553
NEMA Standard: FB-1
UL File Number: E161206
UL Standard: UL-514B
UNSPSC: 39121705

Catalog ID: UCS-150200

UPC Number: 78174702936

Description: One piece clamp back and strap combination,

1 hole, Steel, 1-1/2" - 2" Trade Size.

Application: The one piece clamp back and strap secures both cable and conduit. The UCS-150200 secures 1-1/2" and 2" EMT, Rigid, IMC, Metallic Liquid Tight, Nonmetallic Liquid Tight, FMC, and Schedule 40 and Schedule 80 PVC conduit, as well as 1.735" Ø to 2.450" Ø steel and aluminum AC/MC cable. Plenum Rated for use in Air Handling systems, per UL 2043. Patent Pending

Trade Size: 1-1/2" - 2"

Std Pkg Qty: 25

Unit Qty: 1