



Representative Image

Catalog No. TM2010CCU

Description: 100A 20CT 1P3W 120/240V 22K IC COMB

UPC No 783164112443

 $\label{eq:home} \textbf{Home} > \textbf{Load Centers} > \textbf{Single Phase - USA}$

PowerMark Gold main breaker load centers arrive with a main breaker installed for a convenient and swift install. Main breakers allow for the user to stop the flow of electricity in the load center, shutting off all the power in the residence. The TM2010CCU features spaces for 20, 1" breakers, a 100 A bus ampere rating, a copper bus, and a combination/flush enclosure.

Descriptors	
Category	Single Phase - USA
GO Schedule	RD

Specifications		
Input/Output Voltage	120/240V ac	
Туре	Standard	
Interrupting Capacity Rating	22	
Amperage	100 A	
Device type	Main Breaker	
Enclosure	Indoor Type 1 Enclosure, Combination	
Phase	1 Phase	
1" Space	20	
1/2" Space	0	
Feed	Either	
Door	Yes	
GSA Compliance	Yes	
NEMA Rating	NEMA 1	
Circuit Breaker Style	Plug-In	

Classifications	
UL/CUL Listing	UL

electrification.us.abb.com Created on: 05/14/2022

Publications		
Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers	DET1022	Application and
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Technical
1 page outline drawing in pdf format.	10103091-SH17	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

electrification.us.abb.com Created on: 05/14/2022