



HIGH VOLTAGE TERMINATION (HVT-Z) FOR SHIELDED CABLES

KEY FEATURES

- Co-extruded one-piece termination
- * Built-in stress control
- As an option, the HVT-Z can also be ordered with TE's new line of Aluminum ShearBolt Terminals.
- These are range taking mechanical connectors that will accommodate a conductor range from #2 compact to 1000 kcmil stranded, Class B.

TE Connectivity's (TE) Raychem HVT-Z high voltage termination system features a new, co-extruded one-piece termination. The main termination component consists of the proven Raychem non-tracking tube together with a co-extruded stress control grading layer.

This stress control layer is based on ceramic semi-conductor technology (ZnO) and provides superior discharge and impulse performance. When the tubing is shrunk down, the coating softens and sticks to irregular surfaces, providing moisture seals as well as electrical stress control.

HVT-Z high-voltage terminations are fully qualified per IEEE-48 as Class I terminations to provide a long, trouble-free service life.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

High Voltage Termination (HVT-Z)



PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)					
Indoor Kit	Outdoor Kit	Conductor Size (min. - max.)		Insulation Dia. (min. - max.)	Jacket O.D. (max.)
For Copper Tape Shield, Wire Shield, UniShield, and Lead Sheath Cables					
5/8 kV		5 kV (0.90")		8 kV (0.115")	
HVT-Z-80-G/SG	-	#4-#1 AWG	#6-#2 AWG	0.35-0.60 (9-15)	0.95 (24)
HVT-Z-81-G/SG	-	1/0 AWG-250 kcmil	#1-4/0 AWG	0.60-0.95 (15-24)	1.20 (30)
HVT-Z-82-G/SG	-	300-500 kcmil	250-500 kcmil	0.80-1.25 (20-32)	1.50 (38)
HVT-Z-83-G/SG	-	600-1750 kcmil	600-1750 kcmil	1.10-1.75 (28-44)	2.10 (53)
HVT-Z-84-G/SG	-	1500-3500 kcmil	1500-2500 kcmil	1.60-2.45 (41-62)	2.75 (70)
Installed Length 11.5" (295)		Can be cut shorter for use with MCK kits		No Skirts for Outdoor Operation	
15 kV		15 kV (.175-.220")			
HVT-Z-151-G	HVT-Z-151-SG	#4-1/0 AWG	-	0.60-0.95 (15-24)	1.20 (30)
HVT-Z-152-G	HVT-Z-152-SG	2/0 AWG-350 kcmil	-	0.80-1.25 (20-32)	1.50 (38)
HVT-Z-153-G	HVT-Z-153-SG	400-1000 kcmil	-	1.10-1.75 (28-44)	2.10 (53)
HVT-Z-154-G	HVT-Z-154-SG	1250-2500 kcmil	-	1.60-2.45 (41-62)	2.75 (70)
Installed Length 11.5" (295)				1 Skirt for Outdoor Operation	
25 kV/35 kV		25 kV (0.260")		35 kV (0.345")	
HVT-Z-252/352-G	HVT-Z-252/352-SG	#2 AWG-250 kcmil	#1-1/0 AWG	0.80-1.25 (20-32)	1.50 (38)
HVT-Z-253/353-G	HVT-Z-253/353-SG	300-750 kcmil	2/0 AWG-500 kcmil	1.10-1.75 (28-44)	2.10 (53)
HVT-Z-254/354-G	HVT-Z-254/354-SG	1000-2000 kcmil	750-1750 kcmil	1.60-2.45 (41-62)	2.75 (70)
Installed Length 19.0" (485)				4 Skirts for Outdoor Operation	
Kits Include ShearBolt Terminal					
5/8 kV		5 kV		8 kV	
HVT-Z-81-G/SG-T5	-	1/0 AWG-250 kcmil	#1-4/0 AWG	0.60-0.95 (15-24)	1.20 (30)
HVT-Z-82-G/SG-T5	-	300-350 kcmil	250-350 kcmil	0.80-1.07 (20-27)	1.50 (38)
HVT-Z-83-G/SG-T8	-	350-500 kcmil	350-500 kcmil	0.85-1.25 (22-32)	1.50 (38)
HVT-Z-84-G/SG-T9	-	600-1000 kcmil	600-1000 kcmil	1.10-1.40 (28-36)	2.10 (53)
Installed Length 11.5" (295)				No Skirts for Outdoor Operation	
15 kV		15 kV			
HVT-Z-151-G-T5	HVT-Z-151-SG-T5	#2-1/0 AWG	-	0.65-0.95 (17-24)	1.20 (30)
HVT-Z-152-G-T5	HVT-Z-152-SG-T5	2/0 AWG-350 kcmil	-	0.80-1.25 (20-32)	1.50 (38)
HVT-Z-153-G-T8	HVT-Z-153-SG-T8	400-500 kcmil	-	1.10-1.355 (28-34)	2.10 (53)
HVT-Z-153-G-T9	HVT-Z-153-SG-T9	600-1000 kcmil	-	1.215-1.65 (32-42)	2.10 (53)
Installed Length 11.5" (295)				1 Skirt for Outdoor Operation	
25 kV/35 kV		25 kV (0.260")		35 kV (0.345")	
HVT-Z-252/352-G-T5	HVT-Z-252/352-SG-T5	#2 AWG-250 kcmil	#1-1/0 AWG	0.80-1.25 (20-32)	1.50 (38)
HVT-Z-253/353-G-T5	HVT-Z-253/353-SG-T5	300-350 kcmil	2/0 AWG-350 kcmil	1.10-1.50 (28-38)	2.0 (51)
HVT-Z-253/353-G-T8	HVT-Z-253/353-SG-T8	350-750 kcmil	350-500 kcmil	1.185-1.70 (30-43)	2.10 (53)
HVT-Z-254/354-G-T9	HVT-Z-254/354-SG-T9	600-1000 kcmil	600-1000 kcmil	1.60-1.79 (41-45)	2.75 (70)
Installed Length 19.0" (485)				4 Skirts for Outdoor Operation	

FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 896 089 903
Spain:	+ 34 916 630 400
Benelux:	+ 32 16 351 731
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
China:	+ 86 (0) 400-820-6015

te.com/energy

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. E578 10/2014

Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.