



Catalog No. TLM612FCU

Description: 6CIRC MNLUG 125A INDOOR FLUSH NO DR

UPC No 783164267983

Home > Load Centers > Single Phase - USA

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM612FCU features space for 6, 1" breakers, a 125 A bus ampere rating, a copper bus, and a flush enclosure.

Descriptors

Category	Single Phase - USA
GO Schedule	RD

Specifications

Input/Output Voltage	120/240V ac
Type	Standard
Interrupting Capacity Rating	65
Amperage	125 A
Device type	Main Lug
Enclosure	Indoor Type 1 Enclosure, Flush Mount
Phase	1 Phase
Socket Type	0
1" Space	6
1/2" Space	12
Feed	Either
Door	No
GSA Compliance	No
NEMA Rating	NEMA 1
Circuit Breaker Style	Plug-In

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. 8 Circuit Load Center Fact Sheet	DET1023	Application and Technical
2 page data sheet includes product features, photo, catalog number selection table, knockout drawings, conduit size table, wiring diagrams, accessories and options list. Indoor Load Center	DET-207	Data Sheets
1 page outline drawing in pdf format.	10103091-SH44	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.