

ULTRAQUICK™ INSTALLATION TECHNOLOGY

ULTRA™ Series Ventilation Fans are engineered to be the fastest, easiest, most universal installation in remodel, retrofit and new construction—in any type of joist or truss system. Exclusive features simplify room-side installation to save valuable time and money.

Inside/outside wiring capability provides flexible new or retrofit installation

Pre-installed screws in the mounting frame enable quick installation

Vertical positioning tabs ensure the housing is in the right place

The expandable mounting frame adjusts from 14"–24" and fits any type of joist, I-joist or truss construction



ULTRA PRO FEATURES

- Provide your customers extremely quiet operation with innovative sound reduction technologies
- QStream™ technology features airflow-smoothing baffles to reduce turbulence
- Optional RDFU Premium Radiation Damper Kit available for all XN and ZN models

The preferred install choice for professionals to deliver quiet performance



Ultra Pro Series

Model	Duct Size	CFM	Sones	Light/Night Light	ENERGY STAR®	Housing Dims (in)			Grille Dims (in)		Grille Finish	UL Listed for Tub/Shower use
						W	L	H	L	W		
Single-Speed Fans												
RN80	4"	80	<0.3	—	Yes	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	Yes
RN110	4"	110	0.6	—	Yes	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	Yes
Single-Speed Fan/Lights												
RN80L	4"	80	<0.3	2- 18W GU24 / 4W	Yes	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	Yes
RN110L	4"	110	0.8	2- 18W GU24 / 4W	Yes	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	Yes

ENERGY STAR® fans use 70% less energy, on average, than standard models and may qualify for local utility rebates



SELECTION GUIDE

		57W, 57V	59W	64W, 64V	66W, 66V	68W, 68V	69WL, 69VL	70TW	72W, 72V	77DW, 77DV	78W, 78V	269WL, 269VL	685WL	CFT12WH	82W, DH100W	VS63WH	VS66WH	VS67WH	VS68WH	VS69WH	
Ventilation Fans	682NT		•	•										•		•					
	695, 696N	•	•	•					•						•	•	•				
	LPN80	•		•			•		•						•						
	QT Fans*	•	•	•			•		•		•	•			•	•	•				
	QTXEN110S						•				•										
	RN80, RN110	•	•	•			•		•		•	•			•	•	•				
	XN110H					•	•														
	XN50, XN80, XN110			•			•						•		•						
	ZN110H						•														
	ZN80, ZN110					•							•	•							
	ZN80M, ZN110M					•	•														
Ventilation Fan/Lights	668RP	•	•	•		•			•						•	•	•			•	
	744NT, 744FLNT		•			•									•	•		•		•	
	744SFLNT		•			•										•		•		•	
	763		•	•		•						•			•	•		•		•	
	791LEDNT	•	•	•		•			•			•			•	•		•		•	
	8663RP	•		•	•				•			•			•	•			•		•
	8664RP	•	•	•		•			•			•			•	•		•		•	
	QT Fan/Lights	•		•	•				•			•	•		•	•			•		•
	QTNLEDA, QTNLEDB	•		•	•				•		•				•	•			•		•
	QTXEN110SFLT, QTXN110SL		•							•											
	RN80L, RN110L	•		•	•				•			•	•		•	•			•		•
	XN110HL				•					•											
	XN50L, XN80L, XN110L				•							•	•		•						
	ZN110HL				•																
	ZN80L, ZN110L								•			•									
	ZN80ML, ZN110ML								•												

*Does not include models QT200 and QT300

Fans

Model	Page	CFM	Sones HVI-Certified	Baths up to () Sq Ft	ENERGY STAR®	Duct Size"	Housing Dimensions			Grille Dimensions		Grille finish	Amps
							L"	W"	H"	L"	W"		
682NT	29	—	—	—	No	—	7 ¹ / ₈	7 ¹ / ₈	3 ³ / ₄	8 ¹ / ₂	8 ¹ / ₂	White Polymeric	1.0
690NT	29	60	3.0	55	No	3	See page 29 for compatible models			9 ¹ / ₂	8 ¹¹ / ₁₆	White Polymeric	1.2
695	27	70	6.0	65	No	3	7 ¹ / ₂	7 ¹ / ₄	3 ⁵ / ₈	9 ¹ / ₈	8 ³ / ₄	White Polymeric	1.2
696N	27	50	4.0	45	No	3	7 ¹ / ₂	7 ¹ / ₄	3 ⁵ / ₈	9 ¹ / ₈	8 ³ / ₄	White Polymeric	0.75
AEN80	22	80	0.8	75	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₄	12	White Polymeric	0.3
AEN110	22	110	1.3	105	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₄	12	White Polymeric	0.3
AEN80B	22	80	1.5	75	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₄	12	White Polymeric	0.3
AEN50	22	50	0.5	45	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₄	12	White Polymeric	0.2
AN110	22	110	3.0	105	No	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₄	12	White Polymeric	0.4
LPN80	25	80	1.0	75	Yes	3-4	8	8 ³ / ₄	5 ³ / ₄	13	14	White Polymeric	0.3
QTXEN080	16	80	0.3	75	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	0.4
QTXEN110	16	110	0.7	105	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	0.3
QTXEN110S	18	110	0.7	100	Yes	6	11 ³ / ₄	10 ¹ / ₂	7 ⁵ / ₈	12 ⁷ / ₈	13 ³ / ₄	White Polymeric	0.3
QTXEN150	16	150	1.4	140	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	0.5
RN80	13	80	<0.3	—	Yes	4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	0.3
RN110	13	110	0.6	—	Yes	4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	0.3
XN50	11	50	<0.3	45	Yes	4-6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.1
XN80	11	80	<0.3	75	Yes	4-6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.1
XN110	11	110	<0.3	100	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.2
XN110H	11	110	<0.3	100	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	0.3
ZN80	11	80	<0.3	75	Yes	4-6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.1
ZN80M	11	80	<0.3	75	Yes	4-6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	0.1
ZN110	11	110	<0.3	100	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.2
ZN110H	11	110	<0.3	100	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	0.3
ZN110M	11	110	<0.3	100	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	0.3

Fan/Lights

Model	Page	CFM	Sones HVI-Certified	Baths up to () Sq Ft	Rooms up to () Sq Ft	Lighting Watts Main/Night Light	ENERGY STAR®	Duct Size"	Housing Dimensions			Grille Dimensions		Grille finish	Amps
									L"	W"	H"	L"	W"		
668RP	26	70	4.0	65	85	100W	No	4	14 ⁹ / ₈	7 ⁷ / ₈	5 ⁵ / ₈	16 ¹ / ₄	9 ⁷ / ₈	White Polymeric	2.0
744FLNT	32	70	1.5	65	85	16W floor.	Yes	4	8 ³ / ₄	12 ³ / ₄	6 ³ / ₄	7 ³ / ₈ Dia		White Polymeric	1.2
744LEDNT	32	70	1.5	65	85	14W LED	Yes	4	8 ³ / ₄	12 ³ / ₄	6 ³ / ₄	7 ³ / ₈ Dia		White Polymeric	0.55
744NT	32	70	1.5	65	85	75W	No	4	8 ³ / ₄	12 ³ / ₄	6 ³ / ₄	7 ³ / ₈ Dia		White Polymeric	1.2
744SFLNT	32	70	1.5	65	85	16W floor.	Yes	4	8 ³ / ₄	12 ³ / ₄	6 ³ / ₄	7 ³ / ₈ Dia		Matte White	0.7
763	27	50	2.5	45	60	100W	No	4	8	8 ³ / ₄	5 ³ / ₄	12	10 ⁹ / ₄	White Polymeric	1.6
791LEDNTM	33	110	1.5	95	125	9W LED	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	10 ³ / ₈	10 ³ / ₈	White	0.5
8663RP	26	100	3.5	95	125	100W/7W	No	4	9	9	6	15 Dia		White Polymeric	1.7
8664RP	26	100	3.5	95	125	100W	No	4	9	9	6	15 Dia		White Polymeric	1.7
AN80L	22	80	1.0	75	—	A19 Base	No	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₂	12 ¹ / ₈	White Polymeric	1.2
AN110L	22	110	1.3	105	—	A19 Base	No	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₂	12 ¹ / ₈	White Polymeric	1.2
AN70L	22	70	2.0	65	—	A19 Base	No	4	9 ¹ / ₄	10	5 ³ / ₄	11 ¹ / ₂	12 ¹ / ₈	White Polymeric	1.2
AEN80BL	22	80	1.5	75	—	LED	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ³ / ₄	12 ¹ / ₂	White Polymeric	0.3
AEN80L	22	80	0.8	75	—	LED	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ³ / ₄	12 ¹ / ₂	White Polymeric	0.3
AEN110L	22	110	1.3	105	—	LED	Yes	4	9 ¹ / ₄	10	5 ³ / ₄	11 ³ / ₄	12 ¹ / ₂	White Polymeric	0.3
QTNLEDA	35	110	0.7	100	—	2- 18W GU24	Yes	6 or 4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13 ³ / ₄ SQ	3 ¹ / ₂	White Polymeric	1.0
QTNLEDB	35	110	0.7	100	—	2- 18W GU24	Yes	6 or 4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13 ³ / ₄ SQ	3 ¹ / ₂	White Polymeric	1.0
QTXEN080FLT	17	80	0.3	75	—	2- 18W GU24/4W	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	1.0
QTXEN110FLT	17	110	0.7	100	—	2- 18W GU24/4W	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	1.0
QTXEN110SFLT	18	110	0.7	100	—	2- 18W flour./4W	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	12 ⁷ / ₈	13 ³ / ₄	White Polymeric	1.0
QTXEN150FLT	17	150	1.4	140	—	2- 18W GU24/4W	Yes	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	1.2
QTXN110SL	18	110	0.9	100	—	100W/4W	No	6	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	12 ⁷ / ₈	13 ³ / ₄	White Polymeric	1.0
RN80L	13	80	<0.3	—	Yes	2- 18W GU24	Yes	4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	1.0
RN110L	13	110	0.8	—	Yes	2- 18W GU24	Yes	4	11 ³ / ₈	10 ¹ / ₂	7 ⁵ / ₈	13	14	White Polymeric	1.0
XN110HL	11	110	<0.3	100	—	2- 18W GU24/4W	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	1.0
XN110L	11	110	<0.3	100	—	2- 18W GU24/4W	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.9
XN50L	11	50	<0.3	45	—	2- 18W GU24/4W	Yes	6 or 4	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.7
XN80L	11	80	<0.3	75	—	2- 18W GU24/4W	Yes	6 or 4	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.7
ZN110HL	11	110	<0.3	100	—	2- 18W GU24/4W	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	1.0
ZN110L	11	110	<0.3	100	—	2- 18W GU24/4W	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.9
ZN110ML	11	110	<0.3	100	—	2- 18W GU24/4W	Yes	6	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	1.0
ZN80L	11	80	<0.3	75	—	2- 18W GU24/4W	Yes	6 or 4	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13	14	White Polymeric	0.8
ZN80ML	11	80	<0.3	75	—	2- 18W GU24/4W	Yes	6 or 4	10 ¹ / ₂	11 ³ / ₈	7 ⁵ / ₈	13 ¹ / ₈	14	White Polymeric	0.9