

Catalog No. THQP220

Description: CIRCUIT BRK 10KA QP 2P 120/240V 20A

UPC No 783164085723

Home > Circuit Breakers > Residential Circuit Breakers > Q Line

THQP breakers are a smaller, smarter solution for today's cost- and quality-conscious contractors and homeowners. Half the width and identical in design in comparison to standard breakers, they allow use of smaller load centers and for maximum savings of space and money. GE is the only manufacturer that gives you this cost advantage without sacrificing flexibility. The THQP220 features 1/2" width, 2 poles, an ampere rating of 20 A, an interrupting rating of 10kAlC, and a voltage rating of 120/240V.

Descriptors			
Category	Q Line		
Product Line	Q-Line (Plug-In)		
GO Schedule	R5		

Specifications	
Interrupting Capacity Rating	10 kAIC
Voltage	120/240 V
Trip Style	Non-Interchangeable
Frame Type	Q-Line
Amperage	20 A
System Voltage	120 Vac 120/240 Vac
Poles	2
Trip Function	LI
Continuous Current Rated	Standard
120 Vac Interrupting Rating	10 KAIC
120/240 Vac Interrupting Rating	10 KAIC
Suitable for Reverse Feed	Yes
Wire Range (Cu/Al)	14-8 kcmil / 12-8 kcmil
Long Time	Fixed
Instantaneous	Fixed
Protective Relays	No
Current Metering	No
Special Markings	HACR
GSA Compliance	Yes

Classifications	
UL File #	E11592



Created on: 11/21/2021

Catalog No. THQP220

electrification.us.abb.com

Publications		
Title	Publication No.	Publication Type
PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide	DET1022	Application and
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Q-Line Plug-In MCCB, 100A Frame 1-, 2- Pole, Drawing	DET1023	Technical
1-Page fully dimensioned outline drawing in .pdf format	139C5337-SH1	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

electrification.us.abb.com Created on: 11/21/2021