



### Main

|                       |                           |
|-----------------------|---------------------------|
| Product               | Miniature circuit-breaker |
| Range                 | QO                        |
| Line Rated Current    | 15 A                      |
| System Voltage        | 120/240 V AC              |
| Mounting Type         | Plug-in                   |
| Number of Poles       | 1P                        |
| Circuit Breaker Type  | Tandem                    |
| Ratings               | HACR rated                |
| Electrical Connection | Box lugs                  |

### Complementary

|                        |                                      |
|------------------------|--------------------------------------|
| Interrupt Rating       | 10 kA at: 120/240 V AC 50/60 Hz      |
| Number of Panel Spaces | 1                                    |
| Wire Size              | AWG 14...AWG 8 (copper or aluminium) |
| Height                 | 3.22 in                              |
| Depth                  | 2.91 in                              |
| Width                  | 0.75 in                              |

### Environment

|                |                  |
|----------------|------------------|
| Certifications | CSA<br>UL listed |
| Ambient Rating | 104 °F (40 °C)   |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 1323 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |

---

|                                  |  |
|----------------------------------|--|
| REACH                            | Reference contains SVHC above the threshold - Go to CaP for more details<br><a href="#">Go to CaP for more details</a> |
| Product environmental profile    | Available  |
| Product end of life instructions | Need no specific recycling operations  |

---