



# MT163-W

Lev-Lok Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Modular, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

Mating Lev-Lok Wiring Module Required for Use, Sold Separately

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation. Available in extra heavy duty hospital and industrial grades, and heavy duty commercial grade platforms.

## **Technical Information**

AC Horsepower Ratings Horsepower Rating : 1 HP

Electrical Specifications

#### Amperage : 20 A

**Current Interrupting :** Certified for current interrupting at full rated current **Dielectric Voltage :** Withstands 2000V per UL498

Grounding : Self-Grounding

Maximum Working Voltage : 125V as rated

# **Pole :** 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current Voltage : 125 VAC Wire : 3

# Environmental Specifications

**Operating Temperature :** -40°C to 60°C

Material Specifications
Base Material : Nylon

Cover Material : Nylon Ground Clips : Brass Line Contacts : 0.040" Thick Solid Brass Locking Pins : Solid Brass Mounting Screws : Triple Combination Head, Steel

Mounting Strap : Galvanized Steel with Riveted Ground Contacts

Shutter Mechanism : Delrin® Acetal

Mechanical Specifications **Product ID** : Ratings are permanently marked on device

Termination : Modular


# Product Features Brand : Lev-Lok Decora Plus Color : White

Device Type : Duplex Receptacle Outlet Feature : Tamper-Resistant, Smooth Face

Grade : Heavy-Duty Industrial Specification Grade NEMA : 5-20R

Standards and Certifications ANSI : C-73 NEMA : WD-1 & WD-6 NOM Certified : 057 UL Fed Spec WC-596 : File E13399 Warranty : 10-Year Limited cULus : Listed

# Wiring Diagram



# 5-20

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

